

Product Code: 11002

Luckinslive 405376533

Description: Standard Analogue 1 Module 24 hour Timer



General Information

Dimensions (mm)	90 x 17.5 x 64.5
Display	Mechanical Dial
Time Base	Quartz Crystal
Quartz Crystal Accuracy (at 20°C)	± ± 0.5 Seconds / Day
Materials	Self-Extinguishing Thermoplastic
Mounting	Surface Mounting or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)
Module Size	1
Warranty (Years)	3

Programming

Programming Schedule	24 Hour
Available Operations	96 Operations
Switching Modes	ON, OFF, Permanent On/Off
Minimum Interval (Mins)	15
Program Security	Unlimited (E2-PROM)

Supply & Power

Supply Voltage (V AC)	230
Power Consumption (W)	0.4
Cable Size (mm²)	0.5 - 2.5
Power Reserve	100 Hours (Approx.)

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-5 to +50

Supplied

Accessories

143602: Module Enclosure

Outputs

Number of Outputs	1
Relay/Contact Type	SPST
Total Switch Rating (Inductive)	230V AC, 16A @ 1.0pf 2.5A @ 0.6pf
Maximum LED Lamp Load Rating (W)	200_at_230v
Contact Material	AgSnO²
Maximum Incandescent, Halogen Lamp Load Rating (W)	2000
Maximum Compact Fluorescent Lamp Load Rating (W)	200
Maximum Incandescent Lamp Load Rating (W)	2000
Maximum Fluorescent Lamp (Uncompensated) Load Rating (W)	1000
Maximum Fluorescent Lamp (Series Compensated) Load Rating (W)	750
Maximum Fluorescent Lamp (Parallel Compensated) Load Rating (W)	550
Minimum Switching power (mW)	1000 (10V/10mA)

