



enerflex.

raising the standards



POWER SUPPLIES



1201SM



1205SM



12TENS

SPECIFICATION

- Full current to load
- 12-14VDC adjustable voltage output
- Additional battery charging
- Deep discharge protection
- Current limiting
- Short circuit protection
- 230V fused input
- Mains transient protection
- Compliant to EMC EN61000-6-1 & 3
- **Up to 92% energy efficiency (reduced running costs and lower power usage)**

Available in the following models as standard:
1201SM / 1202SM / 1203SM / 1205SM / 12TENS

FEATURES

- Switchmode technology
- Din rail design for greater versatility
- LED Indicators (mains, batt, output)
- Separate fused main connectors
- Full electronic protection
- Onboard tamper protection
- Converts power more efficiently

Utilising market leading Gallium Nitride technology (GaN)

OTHER PRODUCTS

IPBOX-2



VP-EEB



TLI-45



CDL-300



DIMENSIONS

- 1201SM
• 91H x 67W x 40D (mm) • 144g (Unboxed)
- 1202SM/1203SM/1205SM
• 91H x 84W x 40D (mm) • 198g Unboxed
- 12TENS
• 91H x 150W x 40D (mm) • 380g Unboxed

CONTENTS

- Power Supply Unit
- 2 x Battery Leads (1 x Red, 1 x Black)
- Wiring instructions included



Manufactured by a BSIA Member