



Product Code

F01587

SWITCH POE 8 PORTS

Reference

1587

EAN

8424299015873

Description.

Description

- This switch complies with the IEEE 802.3af/at standard.
- Provides power to IP devices that meet this standard, through one of its 4 PoE ports.
- UP LINK ports are used for interconnection with other devices on the network.
- LEDs built into each port indicate operating status.
- PoE technology allows you to reduce installation costs by avoiding the need to power the devices through external power.

Technical Details

Includes 220V power adapter

- 8 PoE 10/100Mb/s ports (data and power transmission)
- 2 10/100Mb/s ports (UP LINK)
- Allows cable lengths up to 100m
- 30W for each PoE port, for devices that comply with the IEEE802.3af/at (PoE+) standard
- Supports auto-learning and auto-aging of MAC addresses (1K)
- Includes additional installation elements.

TECHNICAL SPECIFICATIONS

Ports	10 10/100Mb/s ports (8 x PoE + 2 x UP LINK) with connection speed auto-negotiation and MDI/MDIX Auto Cross
PoE power supply	IEEE 802.3af/at (1÷8 ports), 52 V DC / 30 W at each port *

Protocols	IEEE802.3, 802.3u, 802.3x CSMA/CD, TCP/IP
Bandwidth	1,6Gbps
Transmission method	Store-and-Forward
Optical indication of operation	Switch power supply Link/Act PoE status
Power supply	~100-240 V; 50/60 Hz; 1,3 A / 52 VDC; 2,3 A external power supply is included.
Operating conditions	Temperature -10°C ÷ 40°C, Relative humidity 5% - 90%, no condensation
Dimensions	W=190, H=28, D=105 [+/- 2mm]
Net/gross weight	1,2/1,4kg
Protection class	EN 60950-1:2007
Storage temperature	-20°C ÷ 60°C

* The given value of 30 W per port is the maximum value. The total power consumption should not exceed 96 W.

APPLICATION

This switch can supply up to 8 MEET devices. These devices can be either KIN PANELS or WIT MONITORS. Just connect each device to the one of the 8 PoE ports of the switch by means of an Ethernet cable.

Furthermore, these devices can also be a MILO PANEL, a MIO MONITOR or a MILO GUARD UNIT. A PoE Splitter Ref. 1498 is required in this case.

The two UP LINK ports can be used to connect another switch.

Accessories included:

- Power supply
- Brackets for rack mounting

Details.

Product measurements (height x

Weight (kg)

1.0579

Packaging measurements

Video Door Entry system

width x depth) mm
190 X 105 28

(height x width x depth) cm
8,7x25,2x20,6

Technologie
MEET