







DB100 / DB125

DOLPHIN ELECTRONIC INFRARED TAP

- > WRAS Approved product
- > Touch Free Tap for ultimate hygiene prevents cross contamination
- > Quality polished or brushed chrome plated brass finishes available from stock Powder coated finishes also available on special order
- > Water Supply: 3/8 inch single inlet cold or pre-mixed a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Flow rate 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order please enquire)
- > Flow time once user's hands are removed from the tap $-\ I$ second (adjustable by using remote control DB51)
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WATI credits
- > Power cable length 3 meters
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > Tap settings can be adjusted manually or by using remote control (DB51)
- > To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on
- > 2 year manufacturer's warranty
- > Max water temperature 70°C
- > Very low energy usage
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this Dolphin Blue tap
- > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits
- > Power connections: soap dispenser: male / power source: female (DB69F)

HEIGHT 172MM
DIAMETER 50MM
PROJECTION 91MM

PRODUCT CODES

DB100C-STL - Polished chrome battery powered

DB100S-STL-2 - Satin chrome battery powered

DB125C-STL - Polished chrome transformer powered

DB125S-STL-2 - Satin chrome transformer powered



