

LHDC TEST OVEN

1m Portable Test Oven 200°C

Description

Commissioning and routine maintenance testing of the Hochiki Analogue Linear Heat Detection Cable systems can be conducted at site by the use of a calibrated 1 metre test oven.

The portable 1 metre test oven concept of testing, allows accessible one metre installed lengths of sensor cable to be subjected to temperatures within the alarm range. Thus confirming correct calibration setting selection and alarm levels in accordance with project specification requirements.

Where sensor cable is installed within hazardous classified areas or may be inaccessible for oven use, an additional one metre length may be 'series' wired with existing cable (sensor and/or interconnecting cables) to allow testing to be carried out local to the electronic interface unit.



Specifications

Ordering Code / Part Number *Stainless Steel Braid	1m Test Oven	700-000
	Red PVC	700-001
	Red PVC S.S*	700-005
	Black Nylon	700-003
	Black Nylon S.S*	700-004
	LDM-519-LP	700-201
	LDM-519-SEN-N	700-305
	LDM-519-ACT-N	700-304
IP Rating	230 / 115 VAC (fuse rated 10A)	
Materials	0 °C to + 200 °C	
Outer Case	Ruggedised Aluminium	
Weight (kg) / Dimensions (mm)	13.55 / 1070 W x 150 H x 130 D	