

EOL TERMINATORS

Stainless Steel 316 End Of Line

Description

The End Of Line (EOL) junction boxes are designed to terminate either Analogue and Digital LHDC. The EOL unit provides fault monitoring on the cable. Analogue EOL units can monitor for both open and closed circuit faults. Digital EOL's monitor for open circuit faults.



Specifications

Ordering Code / Part Number	EOL S.S. 316 with Fire & Fault test key switch Analogue LHDC Digital LHDC with DDL Digital LHDC with DIM	700-515 700-516 700-517
	EOL S.S. 316 (without test) Analogue LHDC Digital LHDC with DDL Digital LHDC with DIM	700-518 700-519 700-520
	Junction Box S.S 316 with Interposing Cable to LHDC Cable in - Plus LHDC Loop LHDC through Connector	700-522 700-523 700-525
IP Rating	IP65	
Materials	Stainless Steel 316	
Glands	1 x M16 Stainless Steel	
Dimensions (mm)	126 W x 126 H x 80 D	

EOL TERMINATORS

Polycarbonate End Of Line

Description

The Polycarbonate EOL is a basic method of terminating either Digital or Analogue LHDC. It is suitable for the majority of applications and can be easily fixed in place.

The Polycarbonate Junction Box is a basic method of jointing either Digital or Analogue LHDC and is supplied with two glands. It can also be used as a connection junction box between an interposing cable and the LHDC.



Specifications

Ordering Code / Part Number	EOL Polycarbonate Analogue LHDC Digital LHDC with DDL Digital LHDC with DIM		700-502 700-503 700-504	
	Polycarbonate Junction Box Interposing Cable to LHDC LHDC through Connector		700-507 700-508	
IP Rating	IP66			
Materials	Polycarbonate			
Glands	EOL	1 x PG 7	Junction Box	2 x PG 7
Dimensions (mm)	120 W x 80 H x 57 D			

EOL TERMINATORS

Aluminium End Of Line

Description

The End Of Line (EOL) junction boxes are designed to terminate either Analogue and Digital LHDC. The EOL unit provides fault monitoring on the cable. Analogue EOL units can monitor for both open and closed circuit faults. Digital EOL's monitor for open circuit faults.



Specifications

Ordering Code / Part Number	EOL Die Cast Enclosure with Fire & Fault Test Switches Analogue LHDC Digital LHDC with DDL Digital LHDC with DIM	700-511 700-513 700-514
IP Rating	IP66	
Materials	Aluminium	
Glands	1 x PG 7	
Dimensions (mm)	75 W x 80 H x 57 D	