

Product Code: 26404

Luckinslive 396761396

Description: Standard 4 Module 4 Channel 7 Day Timer



General Information

Dimensions (mm)	90 x 36 x 63
Display	LCD Display
Time Base	Quartz Crystal
Quartz Crystal Accuracy (at 20°C)	± ± 0.5 Seconds / Day
Materials	Self-Extinguishing Thermoplastic
Mounting	Surface Mounting or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)
Module Size	4
Warranty (Years)	3

Outputs

Number of Outputs	4
Relay/Contact Type	SPDT
Output Relay Resistive Load Rating (A)	16
Output Relay Inductive Load Rating (A)	6
Load Rating Comment	Per Channel
Contact Material	AgSnO ²
Maximum Starting Current (A)	50
Minimum Switching power (mW)	1000 (10V/10mA)

Programming

Programming Schedule	24 Hour, and 7 Day Programmable
Available Operations	300 Operations
Switching Modes	ON, OFF; Pulse, Cycle
Minimum Interval (Mins)	1
Summer/Winter Time Change	Yes (Automatic)
Program Security	Unlimited (E2-PROM)
Pulse length - Pulse function (switching time)	00:01 up to 59.59 mm:ss
Pulse length - Timer (man. switching)	0:00:01 up to 9:59:59 h:mm:ss

Supply & Power

Supply Voltage (V AC)	230
Power Consumption (W)	0.2-1
Cable Size (mm ²)	0.5 - 2.5
Power Reserve	10 Years (Approx.)
Battery Type	Replaceable CR2032
IEC Protection Class	Class II When Installed According to Regulations

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-30 to +55

Accessories

- 143541: Module Enclosure
- 25195: Easy Vue Hub Programming Interface
- 25196: Easy Vue Hub Programming Interface with Bluetooth
- 25193: Programming Interface

