



Product Code

FFR03235

COLOUR BUS2 INDUCTION LOOP LOFT MONITOR

Reference

3235

EAN

8424299032351

Description.

Description

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

A new concept in home monitors. Integrated design, in line with new trends and lifestyles, simple and functional, combining quality and design. The harmony of the gentle, relaxed shapes and the integrated volume concept are the synthesis of LOFT technology and design.

Its purity of line, technology and performance make this equipment an elegant and perfect element for any home.

Made in high impact ABS plastic, with a textured finish for easy cleaning and ultraviolet protection for greater resistance to sunlight.

BUS 2 system: simplified installation system, minimum wiring and powerful features, guaranteeing maximum audio/video signal

quality at all points of the installation. Maximum immunity to outside interference. Lets you manage buildings of up to 199 homes and 2 entrance accesses. Maximum distance from first access to last home: 250 m. BUS2 AMPLIFIER comes complete with built-in voice synthesizer. When the door release is activated a message is heard: "Door open, please close after entering". TV camera included in BUS2 video entry panels is COLOUR as standard issue. Up to 2 terminals (2 telephones, 2 monitors or 1 telephone + 1 monitor) can be installed in each home. The home terminals require simple programming, done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor). Communication is private. Wiring: Audio/Video: 2-wire bus without polarity. We recommend CAT2 twisted pair cable for maximum distances and homes capacity. Maximum distance from first access to last home: 250 m.

Technical Details

Screen TFT 3.5".

Resolution: 480 (H) x 234 (V) lines.

Terminal has a built-in magnet in the earpiece area that ensures the arm is well fitted and fixed to the base. This prevents the arm falling off damaging the wall when hanging up and also avoids faults caused in the installation by being badly hung. Dimensions: 220x203x60 mm (height-width-depth): Power supply: 24 Vdc Door release and guard unit call button. Auto-on button for main and secondary camera activation (sequentially). Call volume control Colour, brightness and contrast control. On/off control Door bell: for direct house call button connection to monitor/telephone. Two selectable call tones. With 2 pushbuttons for additional functions (without functions assigned). Private communication. Conversation secrecy. Consumption:

- in standby: 8 mA

- active: 400 mA

The phone handset comes with a built-in induction loop as standard issue which interacts with the hearing aids of deaf people. The handset is identified with a blue label.

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system
0.787582	27,2x23,9x6,6	Technologie BUS2

Manuals

- https://docs.fermax.com/manuales/97336b%20Monitor%20BUS2%20Ref%203220-3230%20V05_10.pdf,