

**41SAB101B****ADDRESSABLE SOUND BASE EN54-3, BLACK**

The 41SAB101B LOGIFIRE series addressable sounder base has a built-in sounder. A detector can be mounted on it, minimising the space required for installation. Powered directly by the control panel and controlled by means of Comelit communication protocol, it offers 32 different tones and 2 sound levels that can be programmed from the control panel. Base with sounder featuring a modern design suitable for any type of installation, even the most aesthetically demanding cases. A unified design across all sensors in Comelit's new LOGIFIRE range. Mounting on base 41RBX020, 41RBX020H, 41RBX020B, 41RBX020HB or base with flashing light 41VAD100 in compliance with standard EN54-23. Built-in isolator. Certified according to standards EN54-3 and EN54-17. Colour: black.



41SAB101B

ADDRESSABLE SOUND BASE EN54-3, BLACK

MAIN FEATURES

Model	Base with siren, LOGIFIRE series
Backwards compatible with ATENA series control panels	Yes
Number of tones available (n°)	32
Isolator	Yes
EN regulations	EN54-3, EN54-17

HARDWARE SPECIFICATIONS

Compatible base	41RBX020, 41VAD100
IP protection rating	IP21C
Type of finishing materials	ABS
Installation	Ceiling mount
Product color	Black RAL9005
Cross-section for terminals (mm)	0.4 ÷ 2.5
Operating temperature (°C)	-35 ÷ 55
Height base included (mm)	38
Diameter (mm)	121
Product weight (g)	125

ELECTRICAL SPECIFICATIONS

Supply voltage	16 - 32 V CC (Nom. 27 V CC)
Rated absorption (stand-by)	470uA@27VDC
Max. abs. (other tones) high volume (with only audio active)	9,8 mA a 27 V CC
Max. abs. (other tones) low volume (with only audio active)	2,8 mA a 27 V CC
Max. abs. main tone 27 high volume with only audio active	9,8 mA a 27 V CC
Max. abs. main tone 27 low volume with only audio active	2,8 mA a 27 V CC



41SAB101B

ADDRESSABLE SOUND BASE EN54-3, BLACK

ELECTRICAL SPECIFICATIONS

Sound power (other tones) high volume (dB@1m)	~ 87dB (A) ± 3dB @ 1m
Sound power (other tones) low volume (dB@1m)	~ 81dB (A) ± 3dB @ 1m
Sound power (main tone 27) high volume (dB@1m)	~ 88dB (A) ± 3dB @ 1m
Sound power (main tone 27) low volume (dB@1m)	~ 81dB (A) ± 3dB @ 1m