

Superior KeyPad Fibra


Wired keypad with touch buttons

This is a device of the Superior product line. Only accredited Ajax Systems partners can sell, install, and maintain Superior products.




*** Management with codes

- Four types of access codes: general, for registered users, for unregistered users, for RRU
- Remote code and access rights management in Ajax apps



Additional features

- Support for automation scenarios: by arming/disarming, by pressing panic button
- Ability to mute interconnected fire detector alarms




Fibra communication technology

- Up to 2,000 m (6,550 ft) of wired communication range with an Ajax hub¹ or Fibra line extension module
- Encrypted data transmission
- Regular polling to display current device states
- Energy consumption of up to 0.23 W



Sabotage protection

- Passcode guessing protection
- Duress codes to simulate system disarming and activate a silent alarm
- Tamper alarm
- Built-in panic button



Quick installation and setup

- Installation without disassembling the enclosure
- Connecting to a hub via the line scanning feature or QR code
- On-site or remote configuration and testing

Compliance with standards EN 50131 (Grade 3) INCERT SSF NFA2P	Compatibility with hubs  For detailed information, scan the QR code or follow the link: ajax.systems/tools/devices-compatibility/?models=KP.Y.F	Communication with a hub Fibra communication technology Wired connection U/UTP cat.5 4×2×0.51 mm (24 AWG) cable, copper conductor 4×0.22 mm² signal cable, copper conductor Communication range up to 2,000 m up to 6,550 ft With U/UTP cat.5 4×2×0.51 mm (24 AWG) cable	Features Access codes keypad code personal codes for registered users codes for unregistered users RRU codes Duress codes keypad duress code personal duress codes Panic button
Power supply Main power supply 5–26 V$\overline{\text{=}}$, up to 487 mW The device is powered by the hub or Superior LineSupply Fibra	Installation Operating temperature –10 °C to +40 °C 14 °F to 104 °F Operating humidity up to 75%	Enclosure Color white, black Dimensions 150 × 103 × 20 mm 5.91" × 4.06" × 0.79" Weight white device: 181 g (6.38 oz) black device: 165 g (5.82 oz) Protection class IP50 Impact protection IK04	Complete set Superior KeyPad Fibra SmartBracket mounting panel Installation kit Quick start guide

¹ When using a U/UTP cat.5 4×2×0.51 cable.



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/superior-keypad-fibra/

-  support@ajax.systems
-  @AjaxSystemsSupport_Bot
-  ajax.systems