



Product Code

F05281

EXPANSION IP_AXES 4

Reference

5281

EAN

8424299052816

Description.

Description

- Expansion module 4 readers/doors.
- Requires 12Vdc. Consumption: 400 mA.
- 4 Readers.
- 4 Output NA/NC. 12V/1A.
- 4 Inputs for readers.
- RS485 communication with central access control.
- Maximum cable length 750 m.
- Max. 10 IP AXES 4 ref. 5281 for each IP AXES 1_2 ref.5280.
- Protocols: S-BUS, Wiegand and Clock&Data.
- 64 automation.
- IP address integrated in the computer.
- Protocols readers: S-BUS, Wiegand and Clock&Data.
- Licenses activation depending on the number of readers in the installation:

- Ref. 5283 until 10 readers - Ref. 5285 until 80 readers
- Ref. 5284 until 40 readers - Ref 5286 until 140 readers

Technical Details

Maximum power consumption: 400 mA

Supply voltage: 9 – 14VDC

Weight with housing: 200 g

Housing dimensions: 157 x 120 x 30 mm

Operating temperature: - 20°C to + 50°C

Control relay: 1A / 12V – 1A / 24V

Details.

Product measurements (height x
width x depth) mm
120(H) x 157(V) x 30 (P) mm

Weight (kg)
0.3761

Packaging measurements
(height x width x depth) cm
3,6x18x12,8

Video Door Entry system
Technologie
NO PE/VP

Access Control Technology

GENERICA

Manuals

- 97846 EXPANSION IP_AXES PLUS 4 REF.
5281_V06_17.pdf

Declaration of conformity

- DOCF05281EN.pdf

Accessories



F02337
BATTERY 12V 7Ah



F02060
BATTERY ADAPTOR 12 V



F05280
CENTRAL CONTROLLER IP_AXES 1/2+



F05190
CITY KEYPAD READER



F05282
EXPANSION IP AXES I/O



F05293
KEYPAD W/PROXIMITY RESISTANT



F04813
P.S.U. DIN6 100-240VAC/12VDC-2A



F05296
RESISTANT PROX. READER WG



F07461
SKYLINE WG MIFARE/EM PROXIMITY
READER V