

# Specifications



## Eaton 540502FULL-0406X

Eaton, Alarms & signalling devices, Fulleon, ROLP sounder, Shallow white (FW) base

### General specifications

|                             |                               |
|-----------------------------|-------------------------------|
| <b>PRODUCT NAME</b>         | Eaton RoLP Fire alarm sounder |
| <b>CATALOG NUMBER</b>       | 540502FULL-0406X              |
| <b>EAN</b>                  | 8714112033222                 |
| <b>PRODUCT LENGTH/DEPTH</b> | 63 mm                         |
| <b>PRODUCT HEIGHT</b>       | 93 mm                         |
| <b>PRODUCT WIDTH</b>        | 93 mm                         |
| <b>PRODUCT WEIGHT</b>       | 0.178 kg                      |
| <b>CERTIFICATIONS</b>       | Not Applicable                |

## Product specifications

|                                 |                                |
|---------------------------------|--------------------------------|
| NUMBER OF TONES                 | 32                             |
| COLOR HOUSING                   | White                          |
| MATERIAL HOUSING                | Plastic                        |
| SOUND OUTPUT                    | 102 dB                         |
| NOMINAL VOLTAGE                 | 24 V                           |
| TYPE OF CURRENT                 | DC                             |
| ELECTRICITY CONSUMPTION         | 0.012 A                        |
| ALARM CURRENT                   | 32 mA                          |
| CONSTRUCTION MATERIAL           | ABS/FR                         |
| EN CERTIFIED TONES              | 6                              |
| OPERATING TEMPERATURE - MAX     | 70 °C                          |
| OPERATING TEMPERATURE - MIN     | -25 °C                         |
| SYSTEM TOPOLOGY                 | Conventional (Non-Addressable) |
| TONES                           | 32                             |
| VOICE TONES                     | No                             |
| PRODUCT BRANDING                | Eaton                          |
| HUMIDITY (NON CONDENSING) - MAX | 95 %                           |
| HUMIDITY (NON CONDENSING) - MIN | 0 %                            |
| DEGREE OF PROTECTION            | IP54                           |
| EN CERTIFICATION STANDARDS      | EN54 Pt3 (Fire Alarm Sounders) |
| CABLE ENTRY                     | Rear                           |
| SYSTEM WIRING                   | 0.28 - 2.5 mm                  |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

## Resources



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

