

ADPRO® iFT™-E

Remotely Programmable NVR+

Introducing the ADPRO iFT-E Series, the next generation of ADPRO NVR+ platforms, offering low total cost of ownership (TCO) for ADPRO multi-service features, quality, and reliability in a super IP solution.



The ADPRO iFT-E is the “32:32 vision” IP video multi-service platform that runs the powerful XO 5 Security+ Operating System*. It is the only NVR out there that offers full remote monitoring features such as arming/disarming, event quad pictures, and reliable transmission via a proprietary acknowledge protocol. The iFT-E optimizes bandwidth use for high quality recording by multistream camera connections, adapting video transmission to the available bandwidth.

Designed for remote operation, ADPRO iFT-E supports the viewing of video and events through networked clients, including CMS and VMS software and the iTrace mobile application for 24/365 monitoring and control wherever you are. ADPRO Xchange2 also allows you to remotely manage the licensing of additional IP and analytics channels for ultimate flexibility.

FEATURES AND BENEFITS

- Deep Learning LoiterTrace™ for video verified loiter detection with reduced fault alarm and increased detection accuracy
- P2P connection available for easy and flexible remote connection
- End to end secure streaming where video is encrypted (HTTPS) from the camera right through to the viewer to avoid tampering (when connecting with 30s and 60s cameras)⁽⁴⁾
- Support optional self-encryption hard drive for security data at rest to avoid data tempering risk in case hard drive was removed from device⁽⁵⁾.
- The Secure Boot feature helps detect tampering with the boot loaders, operating system files, and unauthorized option ROMs by validating their digital signatures.
- Integration with the Honeywell 30 Series and 60 Series IP cameras, iFT, iFT-E and iFT gateway can be used as part of video systems which comply with NDAA (National Defense Authorization Act) 2019, Section 889.
- Scalable: up to 32 IP cameras and up to 32 analytics channels (32:32 vision)
- Supports up to 32 high-definition analogue cameras over IP via Honeywell Performance Series HQA DVRs.
- Support for all major camera brands: ACTI, Arecont, Avigilon, Axis, Bosch, Brickcom, Hikvision, Hikvision AVE, Honeywell (Performance series⁽²⁾, eQIP Series⁽²⁾, eQIP Series 2019⁽³⁾, HDZ Series⁽²⁾, 30/60 Series⁽³⁾), JVC, Panasonic, Pelco, Samsung, Sanyo, Sony, Uniview⁽³⁾, VISTA⁽³⁾, and FLIR⁽³⁾, and support ONVIF Profile S & T Compliant IP Cameras
- Expandable: up to 168 inputs and 144 outputs (on the box: 8 in / 4 out or 20 in / 8 out depending on model)
- Easy IP camera connection via ONVIF Profile S & T protocol
- Video recording, video analytics, and transmission (all remote monitoring ready)
- Reliable data storage: up to 4 x 16 TB HDD, RAID 1 support (needs minimum 2 equal HDD)
- Integrated xTrace video content analytics (VCA) in XO 5: IntrusionTrace, LoiterTrace and Deep Learning Loiter Trace
- 2-way audio: enables instant remote communication to/from site
- High-level integration with ADPRO PRO E-Passive Infrared (PIR) Detectors, including communication over IP, intelligent double knock, and creep zone alarm
- Mobile apps for remote monitoring, verification, and control
- CMS command and control platforms: VideoCentral Platinum (VCP) and iOS/Android iTrace App
- Open platform: easy integration with third-party software (XO-SDK)
- Superior detection and low false alarm rate with low CapEx. Highest quality of protection at a low TCO.
- Highest site protection: powerful new XO 5 delivering intrusion and loitering analytics.
- Reliability: ADPRO proprietary transmission protocol is 100% reliable with guaranteed alarm reception by acknowledgment and redundant transmission; Site Pulse protocol life check.
- Efficiency: H.264/H.265 video compression and multistream for optimal bandwidth usage while providing the highest quality video for recording and viewing.
- Low TCO: up to 32 IP cameras per device yielding the lowest price per channel.
- Easy management of multiple remote sites improves efficiency and reduces personnel cost. Full remote site surveillance and control, extending human guard surveillance.
- Speed: rapid assessment of video alarm images allows to quickly identify the alarm cause, optimizing real-time intervention while reducing expensive nuisance alarm responses.
- Alarm reception in less than 7 seconds.
- Extremely fast, intelligent search on motion metadata after recording.
- VMD: 4 zones per camera.
- User-friendly: easy-to-use XO client for configuration and management.
- Xchange2 for adding video and VCA licenses
- Bulk firmware upgrade remotely
- Supporting new licensing type switchable between LoiterTrace and IntrusionTrace.
- 360° camera support + image de-warping: see everything, everywhere, always.

(1) If a 12 Megapixel IP camera is used with the XO enabled iFT-E Series, then a maximum of 12 cameras, with a maximum of 12 video analytics channels (IntrusionTrace and/or LoiterTrace) can be used.

(2) The Honeywell Performance, eQIP, and HDZ series IP cameras are supported from version XOa 3.2.33.

(3) The Uniview, Honeywell eQIP Series 2019 and 30 Series, VISTA, and FLIR cameras are supported from version XO 4.5.

(4) When secure streaming is enabled. Audio back from XO Client/ CMS to cameras will be disabled.

(5) Encryption hard drive feature is only available when products ordered together with the SED hard drives.

ADPRO® IFT-E

SPECIFICATIONS	
OPERATIONAL	
OPERATING SYSTEM	ADPRO® XO™ Security Operating System, Linux based
VIDEO INPUT	1–32 IP cameras
VIDEO OUTPUT	XGA – Multiple matrix type views
VIDEO COMPRESSION	H.264/H.265*
VIDEO RESOLUTION	Up to HD/MP resolution**
IMAGES/SECOND	Full HD @25/30 ips – MPixel: ips is camera dependent
BANDWIDTH CAPACITY	32 x 5 Mbps
BANDWIDTH MANAGEMENT	Configurable variable or constant bitrate / Configurable bandwidth limiter
AUDIO INPUT	Built-in audio input supported***
AUDIO OUTPUT	Standard 1 line level output. Optional: up to 1 per camera via audio switcher(s). Audio out on IP cameras** with ONVIF Profile S driver
COMMAND INPUTS	8 or 20 inputs on the box depending on model (monitored), + 20 inputs (monitored) via XO I/O Interface USB module, Via Network I/O module with PoE: up to 128***
RELAY OUTPUTS	4 or 8 outputs on the box (SPDT) depending on model, + 8 outputs (SPDT) via XO I/O Interface USB module Via Network I/O module with PoE: up to 128 (SPDT)
WEB SERVER	XO client – integrated web client application (ActiveX)
ETHERNET	2 x 100/1000BASE-T, autodetection, full duplex, RJ45
RECORDING TYPE	Schedule / Detection / Event
IP CAMERA INTEGRATION	Brand specific, Generic, support ONVIF Profile S & T** cameras
MANAGEMENT	Web client interface (XO client), ADPRO VideoCentral Platinum, third-party software (SDK available) and iOS/Android iTrace App.
POWER SUPPLY	100–240 VAC, 50/60 Hz
OPERATING TEMPERATURE	5–40 °C
HUMIDITY	20–93 % RH non-condensing
DISK CAPACITY	Max. 4 x 16 TB HDD RAID 1 support (= min. 2 equal HDD) Support Self-Encryption Hard Drive (SED)
WARRANTY	2 years
DIMENSIONS (W X H X D)	441 x 88 x 305 mm (17.36" x 3.46" x 12.00")
ANALYTICS	Basic motion detection (VMD), camera sabotage detection. Up to 32 analytic channels for IntrusionTrace™, LoiterTrace™ and up to 4 channels of Deep Learning LoiterTrace™. Totally up to 32 Analytics channels supported (separate datasheets available)
MOBILE APPS	iTrace, iPIR

* H.265 supported with Honeywell, Hikvision, ONVIF and generic drivers.

** Camera dependent. List of supported IP cameras is available on www.security.honeywell.com

*** Monitored or unmonitored inputs depending on Net I/O unit V2 hardware and V2 firmware.

ORDERING INFORMATION	
63021510	ADPRO iFT-E 8IP-4TB-8inputs/4outputs (4 HDD ready)
63045720	New ADPRO iFT-E 16IP-1x8TB-HDD-SED-20inputs/8outputs (4HDD Ready)
63041610	ADPRO iFT-E 16IP-6TB-8inputs/4outputs (4 HDD ready)
63041810	ADPRO iFT-E 16IP-10TB-8inputs/4outputs (4 HDD ready)
63001820	ADPRO iFT-E 0IP-10TB-20inputs/8outputs (4HDD Ready)
63040020	ADPRO iFT-E 16IP-No HDD-20inputs/8outputs (4HDD Ready)
63041620	ADPRO iFT-E 16IP-6TB-20inputs/8outputs (4HDD Ready)
63081020	New ADPRO iFT-E 32IP-No HDD-20inputs/8outputs (4HDD Ready)
63086720	New ADPRO iFT-E 32IP-2x8TB-HDD-SED-20inputs/8outputs (4HDD Ready)
63081820	ADPRO iFT-E 32IP-10TB-20inputs/8outputs (4HDD Ready)
63082620	ADPRO iFT-E 32IP-2x6TB-20inputs/8outputs (4HDD Ready)

Find out more:

www.security.honeywell.com

Honeywell Commercial Security

715 Peachtree St. NE

Atlanta, GA 30308

1.800.323.4576

www.honeywell.com

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

The Sooner You Know, VESDA-E, VESDA, ICAM, ECO, OSID, HeiTel, ADPRO, IntrusionTrace, LoiterTrace, XOa, XOh, iTrace, iPIR, and FMST are trademarks and/or registered trademarks of Honeywell and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label.

HSV-ADPROIFTE-07-US(0121)DS-Z
© 2021 Honeywell International Inc.

Mobile Apps

- iTrace: remote monitoring, verification, and control (iOS and Android).
- iPIR: allows one person to commission ADPRO PRO E-PIRs: wireless walk testing and parameter adjustment (iOS).

XO Security Operating System

The XO Security Operating System expands the feature-rich, multi-service capability of the ADPRO NVRs. XO enables an iFT-E to support up to 32 IP camera channels with up to 32 analytics channels simultaneously allowing a customer to leverage xTrace analytics for intrusion & loitering detection and building management capabilities while providing immediate remote response. It provides live 24/365 unbreakable transmission of very high quality video events to remote monitoring stations; providing deterrence through multi-level response, including audio, lighting/door controls, HVAC, as well as first responder dispatch. XO provides the first technology solution to effectively augment human guards security with intelligent and accurate detection more cost effectively with higher reliability. Customers deploying XO can employ a "pay as you grow" security approach, using analytics where and when they are needed.

xTrace Analytics

Add-on video analytics:

- IntrusionTrace: outdoor video verified perimeter detection for sterile zone monitoring (car dealerships, solar parks, power generation facilities, and warehouses) ; i-LIDS certification
- LoiterTrace: video verified loitering detection for indoor & outdoor applications (graffiti, parks, carparks, school grounds and construction areas).

The New Analytics Feature for ADPRO allows the customer to order a VCA License with the ability to switch each channel individually between LoiterTrace and IntrusionTrace at any time, saving the need to purchase separate licenses.

Deep learning LoiterTrace

Add-on video analytics:

- AI Enabled Loiter Detection
- Leveraging the latest tech break through in artificial intelligence, deep learning enabled LoiterTrace improves detection and reduce fault alarm by tracking individual instead of group, improved accuracy of classification for people/object. Efficiently prevents damage & reduces risk: Vandalism, graffiti, substance abuse, arson attacks, harassment, identity theft

Honeywell