



Product: [70049LW](#)

1 PAIR AES/EBU, 24AWG, ISTP, LSZH

Product Description

DIGITAL AUDIO 1 PAIR AES/EBU, 24AWG/0.22mm², ISTP, LSZH

Technical Specifications

Product Overview

Suitable Applications:	1-pair 24AWG halogen-free single pair cable; For digital audio
------------------------	--

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Construction n x D	No. of Pairs
24	7x32	BC-OFHC - Oxygen-Free Bare Copper (High Conductivity)	7x0.20 mm	1
Conductor Count:		2		
Total Number of Pairs:		1		

Insulation		
Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene (Foam)	1.70 mm	0.05 mm

Color Chart	
Number	Color
Pair 1	Red & Black

Outer Shield						
Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	Drainwire Position
Tape	Bi-Laminate (Alum+Poly)	100%	TC - Tinned Copper	24	7x0.20 mm	Under shielding foil

Outer Jacket		
Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.9 mm	0.3 mm

Construction and Dimensions

Cabling	
Description	1 pair + drainwire stranded tinnend copper (AWG24)(7x0.20mm)

Electrical Characteristics

Conductor DCR	
Nominal Conductor DCR	86 Ohm/km

Capacitance	
Nom. Capacitance Conductor to Conductor	36 pF/m

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
0.1 - 6	110 Ohm	15 Ohm

Delay

Nominal Velocity of Propagation (VP) [%]
76%

Temperature Range

Other Temp Range:	-30-+70 °C
-------------------	------------

Mechanical Characteristics

Max. Pull Tension:	70 N
Min. Bend Radius During Installation:	70 mm
Min. Bend Radius During Operation:	100 mm

Standards

CPR Euroclass:	Cca-s1,d1,a1
----------------	--------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Cca
----------------------	------------------------

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2, IEC 60332-3-24
IEC 60754-1 - Halogen Amount:	zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3

History

Update and Revision:	Revision Number: 0.42 Revision Date: 02-15-2024
----------------------	---

© 2025 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.