

Product Code: 72102NFC

Luckinslive 404055198

Description: Astro 2 Module 1 Channel 24 Hour Timer, Near Field Communication (NFC)



General Information		Outputs	
Dimensions (mm)	90 x 36 x 63	Number of Outputs	1
Display	LCD Display	Relay/Contact Type	SPDT
Time Base	Quartz Crystal	Relay Voltage - Maximum (AC)	230
Quartz Crystal Accuracy (at 20°C)	± ± 0.5 Seconds / Day	Maximum LED Lamp Load Rating (W)	200 @ 230V
Astro Zone	User Defined	Contact Material	AgSnO ²
Astro Offset Switching Time (Mins)	(+/-) 90	Maximum Inductive Current Rating (A) (0.8pf)	10 @ 0.6pf
Materials	Self-Extinguishing Thermoplastic	Maximum Incandescent, Halogen Lamp Load Rating (W)	2000
Mounting	Surface Mounting or DIN	Maximum Compact Fluorescent Lamp Load Rating (W)	200
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)	Maximum Fluorescent Lamp (Uncompensated) Load Rating (W)	1000
Module Size	2	Maximum Fluorescent Lamp (Series Compensated) Load Rating (W)	1000
Warranty (Years)	3	Maximum Fluorescent Lamp (Parallel Compensated) Load Rating (W)	550
Programming		Minimum Switching power (mW)	1000 (10V/10mA)
Programming Schedule	24 Hour		
Available Operations	4 Operations		
Switching Modes	Astro ON/OFF, Night ON/OFF		
Minimum Interval (Mins)	1		
Summer/Winter Time Change	Yes (Automatic)		
Program Security	Unlimited (E2-PROM)		
Pulse length - Pulse function (switching time)	00:01 up to 59.59 mm:ss		
Pulse length - Timer (man. switching)	0:00:01 up to 9:59:59 h:mm:ss		
Supply & Power			
Supply Voltage (V AC)	230		
Power Consumption (W)	0.2-1		
Cable Size (mm²)	0.5 - 2.5		
Power Reserve	10 Years (Approx.)		
Battery Type	Replaceable CR2032		
IEC Protection Class	Class II When Installed According to Regulations		
Environment			
Ingress Protection	IP20		
Operating Temperature (°C)	-30 to +55		
Features		Accessories	
Volt-Free 16A Changeover Contact		143602: Module Enclosure	
4 Memory Locations			
Basic Astro Programming			
Works with Android NFC Phones for Programming			
Battery Reserve: 10 years			

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN