

# Specifications



## Eaton 811013FULL-0007

Eaton, Alarms & signalling devices, Fulleon, Solista LED beacon, Red lens, Red housing, Deep red base

### General specifications

|                      |                                 |
|----------------------|---------------------------------|
| PRODUCT NAME         | Eaton Solista Fire alarm beacon |
| CATALOG NUMBER       | 811013FULL-0007                 |
| EAN                  | 8714112068965                   |
| PRODUCT LENGTH/DEPTH | 83 mm                           |
| PRODUCT HEIGHT       | 93 mm                           |
| PRODUCT WIDTH        | 93 mm                           |
| PRODUCT WEIGHT       | 0.125 kg                        |
| COMPLIANCES          | EN 50130-4:2011                 |
| CERTIFICATIONS       | Not Applicable                  |

| Product specifications          |                                |
|---------------------------------|--------------------------------|
| NOMINAL VOLTAGE                 | 24 V                           |
| VOLTAGE TYPE                    | DC                             |
| ELECTRICITY CONSUMPTION         | 0.005 A                        |
| POWER                           | 0.12 W                         |
| LENS COLOR                      | Red                            |
| MATERIAL HOUSING                | Plastic                        |
| COLOR HOUSING                   | Other                          |
| MOUNTING METHOD                 | Surface mounting               |
| NUMBER OF MODES                 | 4                              |
| STANDBY-TIME UP TO              | 0 hour                         |
| AMBIENT TEMPERATURE - MAX       | 55 °C                          |
| AMBIENT TEMPERATURE - MIN       | -10 °C                         |
| LAMP TYPE                       | LED not exchangeable           |
| LAMP HOLDER                     | Other                          |
| DEGREE OF PROTECTION (IP)       | IP33                           |
| ADDRESSING MODE                 | Hard addressing                |
| ALARM CURRENT - MAX             | 10 mA                          |
| ALARM CURRENT - MIN             | 5 mA                           |
| CONSTRUCTION MATERIAL           | ABS/FR                         |
| HUMIDITY (NON CONDENSING) - MAX | 95 %                           |
| HUMIDITY (NON CONDENSING) - MIN | 0 %                            |
| OPERATING TEMPERATURE - MAX     | 55 °C                          |
| OPERATING TEMPERATURE - MIN     | -10 °C                         |
| STANDBY CURRENT                 | 0                              |
| SYSTEM TYPOLOGY                 | Conventional (Non-addressable) |
| PRODUCT BRANDING                | Eaton                          |
| INTEGRATED FUNCTION             | Flashlight                     |
| CABLE ENTRY                     | M20 hole                       |
| MOUNTING POSITION               | Wall (weatherproof)            |
| LIGHT COLOR                     | Red                            |
| SYSTEM WIRING                   | 0.5 - 2.5 mm                   |
| DIMMABLE                        | No                             |
| FUNCTION ROTATING LIGHT         | NO                             |
| WITH INFRARED                   | NO                             |

| Resources             |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| TECHNICAL DATA SHEETS | <a href="#">eaton-fire-devices-beacon-solista-datasheet-2009.pdf</a> |

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights  
Reserved.

Eaton is a registered trademark.

All other trademarks are property of  
their respective owners.

Follow us on social media to get the latest  
product and support information.

