

Eaton 812015FULL-0116X

Catalog Number: 812015FULL-0116X

Eaton, Alarms & signalling devices, Fulleon, Solista LX Wall LED beacon, Red flash, White housing, Shallow white (W1) base (I SOL-LX-W/RF/W1/S)

General specifications

Product Name	Catalog Number
Eaton Solista LX Visual alarm beacon	812015FULL-0116X
EAN	Product Length/Depth
8054934906541	37 mm
Product Height	Product Width
93 mm	93 mm
Product Weight	Certifications
0.1 kg	CE

Product specifications

Nominal voltage

24 V

Voltage type

DC

Electricity consumption

0.025 A

Power

1.5 W

Lens color

Clear

Material housing

Plastic

Color housing

White

Mounting Method

Surface mounting

Number of modes

4

Standby-time up to

0 hour

Ambient temperature - max

70 °C

Ambient temperature - min

-25 °C

Lamp type

LED not exchangeable

Lamp holder

Other

Degree of protection (IP)

IP33

Addressing mode

Hard addressing

Alarm current - max

51 mA

Alarm current - min

Resources

Technical data sheets

[eaton-fire-alarm-beacon-solista-lx-wall-datasheet-2014-en.pdf](#)

9 mA

Construction material

ABS/FR

Humidity (Non Condensing) - Max

95 %

Humidity (Non Condensing) - Min

0 %

Operating temperature - max

70 °C

Operating temperature - min

-25 °C

Standby current

0

System typology

Conventional (Non-addressable)

Product branding

Eaton

Nominal voltage - min

12 V

Nominal voltage - max

48 V

Electricity consumption - min

0.018 A

Electricity consumption - max

0.051 A

Integrated function

Flashlight

EN Certification Standards

EN54 Pt23 (Visual Alarms)

Cable entry

Rear

Mounting position

Wall surface (internal)

Wall (weatherproof)

Light color

Red

System wiring

0.5 - 2.5 mm



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia