

APERTA IP

Product Code: A1IPDSM1

Description: Aperta IP PoE Multi Way Outdoor Station HD with Proximity Reader

Technical Specification Single Way IP Video Door Entry

Luckinslive 435691356

ESP
ScolmoreGROUP



General Information

Dimensions (mm)	365 x 140 x 50
Finish	Brushed Silver
Materials	Aluminium Alloy
Mounting	Surface & Flush
Fob Reader Operating Frequency	13.56MHz
Fobs Supported	200
Warranty (Years)	2

Media Information

Camera	1.0MP CMOS Low Illumination
Screen Size (Inches)	4.3" Colour TFT LCD
Video Compression	H.264
Viewing Angle (°)	90 (Horizontal)
Audio	Noise Suppression & Echo Cancellation

Programming

User Interaction	Keypad & GUI via LCD Screen
PIN Length	6

Environment

Ingress Protection	IP65
Impact Rating (IK)	IK10
Operating Temperature (°C)	-10 to +50
Relative Humidity Resistance (%)	<90

Supply & Power

Operating Voltage (V DC)	15
Secondary Power Source	PoE 802.3af/at
Power Consumption (mA)	<150
Lock output	12VDC, NO & NC Contacts

Network

Network Rate (Mbps)	10/100/1000 Mbps Self-adaptive Ethernet
---------------------	---

Supplied Weather Shield & Mounting Casing, 4 x Double Terminal Blocks, 1 x Triple Terminal Block, 7 core Cable (1m), 4 core cable (1.0m), Screw & Rawl plug pack, Foam Gasket, Quick Start Guide


Features

Built-in Keypad & Fob reader for unlocking door
Audio message alerts user if the door has been unlocked.

Accessories

A1IPT10: Aperta IP 13.56MHz Pack of 10 Tags

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN