

**Code: ADCN412G**

Mortice Electric Release 12V DC Fail Locked, Continuously Rated - Stainless Steel

A range of cost effective Dorcas electric releases for use with 12 & 24V Access Control and Door Entry Systems on timber doors. Designed for use with mortice nightlatches and latches, the mortice electric release is fitted in place of the normal strike. Generally suitable for inward or outward opening doors.

Features & Benefits

- Suitable for low to medium traffic applications
- Fail locked & unlocked versions
- Suits latches with 12mm maximum throw
- Jaw strengths up to 880lbf (362kgf/256N)
- Operating voltage 12V AC, 12V DC or 24V DC
- Faceplate in Stainless steel finish
- Remain open function available
- For use with timber doors
- Universal for left & right hand doors



CQR Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH
Sales: +44(0)151 6061000 (9am to 5pm Monday to Friday) **Tech:** +44(0)151 606 6311
sales@cqr.co.uk | www.cqr.co.uk

Company Registration Number: 5192024 | VAT Number: 309 0409 27



- 12V DC & 24V DC versions have
Continuously rated solenoid for prolonged
power applications

Product Information

Status	Unmonitored
Brand	Dorcas
Type Of Release	Mortice
Fail Type	Fail Locked
CE Mark	CE
Finish	Stainless Steel

Technical Data

Nominal Holding Force	875 lbf (3900N) (397 kgf)
-----------------------	---------------------------

Environmental

IP Rating	No
Operating Temperature	-25 to +50 °C

Housing

Release Size (mm)	H160 x W25 x D31
Max Latch Projection (mm)	12

Electrical

Voltage	12V DC
---------	--------

Certifications

EMC	EMC
-----	-----

