



General Information

Dimensions (mm)	200 x 87 x 53
Materials	Aluminium Alloy
Mounting	Surface & Flush (requires APDSKPFMS) Mounted
Reader Frequency (KHz)	125
Reader Effective Distance (mm)	<50
Fobs Supported	999
Weight (Kg)	.064
Warranty (Years)	2

Media Information

Illumination	5 White light LEDs
Resolution	700TVL
Sensitivity (Lux)	0.1
Sensor Size (")	1/3
Lens size (mm)	3.6
Viewing Angle (°)	70
Audio	Full Duplex

Programming

User Interaction	0 - 9, * and Bell
Code Lengths	2 - 6
PIN Length	4 or 6
Maximum Call-able address	32
Maximum Access Codes	32 PINs, (99 when set to multi-way), (10 when set to single-way) and 10,000 Tags

Environment

Ingress Protection	IP55
Operating Temperature (°C)	-20 to +40

Supply & Power

Operating Voltage (V DC)	24 (BUS)
Global Selections	Normally Open or Normally Closed; Volt-Free or 12V DC300mA
Effective Distance to PowerSupply (M)	50
Lock outputs	2

Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS

Supplied Fixing Screws, and Wall Plugs, User Manual, 10 x Access Fobs, 1 x Green Programming add Fob, 1 x Red Programming removal Fob

Features

Outdoor Station rings so that the user knows whether the call has been answered, calls last up to 30 seconds

Accessories

EZT3ST10: 10x Proximity Tags
 EVBP5BB: 12V Lock power supply with battery backup
 APPOWMW: Aperta Multiway BUS power supply
 APSEPMW: Aperta Multiway BUS Separator
 APMONW, APMONB, APMONWG, APMONBG, APAUDH, APAUDHBLK:
 Compatible Aperta Monitors
 ENTERD: Flush Electric Lock
 ENTERD-YLR: Surface Electric Lock

Additional Information Simple 2-core Installation
 High-Resolution Colour Camera
 Can call addresses 1 to 32

