

APERTA

Product Code: APDSSW

Description: 1 Way Video Door Station

Technical Specification

Single Way Video Door Entry

Luckinslive 402889230

ESP
ScolmoreGROUP



General Information

Dimensions (mm)	165 x 85 x 53
Materials	ABS
Mounting	Surface Mounting
Weight (Kg)	.39
Warranty (Years)	2

Media Information

Illumination	5 White light LEDs
Resolution	700TVL
Sensitivity (Lux)	0.1
Sensor Size (")	1/3
Lens size (mm)	3.6
Audio	Full Duplex

Environment

Ingress Protection	IP55
Operating Temperature (°C)	-20 to +40

Supplied Fixing Screws, and Wall Plugs, User Manual

Supply & Power

Operating Voltage (V DC)	24 (BUS)
Global Selections	Normally Open or Normally Closed; Volt-Free or 12V DC300mA
Effective Distance to PowerSupply (M)	50
Lock outputs	2

Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS

Features

Outdoor Station rings so that the user knows whether the call has been answered, calls last up to 30 seconds

Accessories

EVBPSSBB: 12V Lock power supply with battery backup
APPOWSWDR: Din Mounted BUS power supply
APMONW: Aperta BUS Monitor in white
APMONB: Aperta BUS Monitor in Black
APMONWG: Aperta GUI BUS Monitor in white
APMONBG: Aperta GUI BUS Monitor in Black
APAUDH: Aperta BUS Audio Only Handset in White
APAUDHBLK: Aperta BUS Audio Only Handset in Black
ENTERD: Flush Electric Lock
ENTERD-YLR: Surface Electric Lock

Additional Information Simple 2-core Installation
High-Resolution Colour Camera

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN