



General Information

Dimensions (mm)	170 x 90 x 42
Materials	ABS
Mounting	Surface or DIN Rail
Warranty (Years)	2

Environment

Ingress Protection	IP20
--------------------	------

Supply & Power

Operating Voltage (V DC)	24
BUS Output	Creates BUS for use with Aperta BUS systems
Effective Distance to Doorstation (M)	50

Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS
Maximum Wiring Distance (m)	100

Accessories

- APMONW: Aperta BUS Monitor in white
- APMONB: Aperta BUS Monitor in Black
- APMONWG: Aperta GUI BUS Monitor in white
- APMONBG: Aperta GUI BUS Monitor in black
- APAUDH: Aperta BUS Audio Only Handset in White
- APAUDHBLK: Aperta BUS Audio Only Handset in Black
- APDSMW: Aperta BUS Multi Way Door Station
- APDSPXMW: Aperta BUS Multi Way Proximity Door Station
- APBC4MW: Aperta 4-Way Branch Controller

Additional Information Simple 2-core Installation
DIN Rail or Surface mount
For use with Multi-way Aperta Applications



Catalogue



DoC



CLICK OR SCAN

CLICK OR SCAN