

Product Code: CHOICE RSTAT5RF

Luckinslive 405496303

Description: Wireless Digital Display Programmable Thermostat



Component 1

Wireless Digital Programmable Thermostat Transmitter

Quantity

1

General Information

|                          |                          |
|--------------------------|--------------------------|
| Dimensions (mm)          | 110 x 104 x 21.5         |
| Colour                   | White                    |
| Materials                | ABS                      |
| Mounting                 | Surface or free standing |
| Call for Heat Indication | LCD Display              |

Supply & Power

|                       |          |
|-----------------------|----------|
| Battery Specification | AAA (x4) |
| Battery Low Indicator | Yes      |

Programming

|                                   |                                |
|-----------------------------------|--------------------------------|
| Adjustment Type                   | Comfort / Economy              |
| Programming Schedule              | 24 Hour or 7 Days              |
| Set Temperature Range (°C)        | 0 to 50                        |
| Temperature Display Range (°C)    | 5 to 35                        |
| Temperature Swing Adjustment (°C) | +/-0.5 or +0/-0.1 (Selectable) |
| Minimum Interval (Mins)           | 10                             |
| Timing Accuracy                   | <1 sec Per Day                 |

Transmission

|                                 |     |
|---------------------------------|-----|
| Transmission Frequency (MHz)    | 868 |
| Wireless Range - Open Field (m) | 80  |
| Wireless Range - Indoor (m)     | 30  |

Environment

|                            |           |
|----------------------------|-----------|
| Frost Protection           | Yes (5°C) |
| Ingress Protection         | IP30      |
| Operating Temperature (°C) | 0 to +50  |

Component 2

Wireless Thermostat Receiver

Quantity

1

General Information

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Dimensions (mm)                 | 88 x 88 x 39.4                      |
| Colour                          | White                               |
| Materials                       | ABS                                 |
| Mounting                        | Surface                             |
| Supply Voltage (V AC)           | 230                                 |
| Frequency (Hz)                  | 50                                  |
| Cable Size (mm²)                | 0.5- 1.5 (Flex)<br>0.5- 2.5 (Rigid) |
| Network Connection Type         | Radio Frequency                     |
| Transmission Frequency (MHz)    | 868                                 |
| Wireless Range - Open Field (m) | 80                                  |
| Wireless Range - Indoor (m)     | 30                                  |
| Output Relay Rating             | 16A (@250V AC) Volt Free Contact    |
| IEC Protection Class            | II                                  |
| Ingress Protection              | IP30                                |
| Operating Temperature (°C)      | 0 to +50                            |

Warranty Years 3

