

Product Code: CHPRSTATDPRF

Luckinslive 423486984

Description: Wireless Thermostat with Programmable Schedules and Digital Display



Component 1

Quantity

Wireless Digital Programmable Thermostat Transmitter

1

General Information

|                          |                                                           |
|--------------------------|-----------------------------------------------------------|
| Dimensions (mm)          | 140 x 88.6 x 32.1 (Without Back Box)                      |
| Colour                   | White                                                     |
| Materials                | ABS                                                       |
| Mounting                 | Surface or Free Standing                                  |
| Call for Heat Indication | LCD Display                                               |
| Sensor Type              | Electronic Sensor for Accurate and Responsive Performance |

Supply & Power

|                       |                                                            |
|-----------------------|------------------------------------------------------------|
| Battery Specification | AA (x4)                                                    |
| Battery Low Indicator | Yes                                                        |
| EE Class              | ErP Class IV                                               |
| Class Description     | TPI Room Thermostat, for use with ON/OFF Heaters, Value 2% |

Programming

|                                                                   |                                                                       |
|-------------------------------------------------------------------|-----------------------------------------------------------------------|
| Adjustment Type                                                   | Digital Programming with Digital Display                              |
| Programming Schedule                                              | 24 Hour or 7 Days                                                     |
| Set Temperature Range (°C)                                        | 5 to 35                                                               |
| TPI (Time Proportional & Integral) Control for Heating Efficiency | Yes                                                                   |
| Temperature Display Range (°C)                                    | 0 to 50                                                               |
| Temperature Swing Adjustment (°C)                                 | 0.5 and 1                                                             |
| Optimisation                                                      | Optimum Start/ Delay Start and Optimum Stop for Additional Efficiency |
| Modes Available                                                   | 3 (Permanent, Timed, and Temporary Override)                          |
| Pre-Programmed Schedule                                           | Yes                                                                   |
| Summer/Winter Time Change                                         | Yes (Automatic)                                                       |

Transmission

|                                 |     |
|---------------------------------|-----|
| Transmission Frequency (MHz)    | 868 |
| Wireless Range - Open Field (m) | 80  |
| Wireless Range - Indoor (m)     | 30  |

Environment

|                            |           |
|----------------------------|-----------|
| Frost Protection           | Yes (5°C) |
| Ingress Protection         | IP30      |
| Operating Temperature (°C) | 0 to +50  |

Component 2

Quantity

Wireless Thermostat Receiver

1

General Information

|                                    |                                                            |
|------------------------------------|------------------------------------------------------------|
| Dimensions (mm)                    | 88 x 88 x 39.4                                             |
| Colour                             | White                                                      |
| Materials                          | ABS                                                        |
| Mounting                           | Surface or Flush (Surface backbox included)                |
| Flush Mounting Back Box Depth (mm) | 25                                                         |
| Sensor Type                        | Electronic Sensor for Accurate and Responsive Performance  |
| Supply Voltage (V AC)              | 230                                                        |
| Frequency (Hz)                     | 50                                                         |
| Network Connection Type            | Radio Frequency                                            |
| Transmission Frequency (MHz)       | 868                                                        |
| Wireless Range - Open Field (m)    | 80                                                         |
| Wireless Range - Indoor (m)        | 30                                                         |
| Output Relay Rating                | 16A Contact Rating (Volt Free)                             |
| IEC Protection Class               | II                                                         |
| EE Class                           | ErP Class IV                                               |
| Class Description                  | TPI Room Thermostat, for use with ON/OFF Heaters, Value 2% |
| Ingress Protection                 | IP30                                                       |
| Operating Temperature (°C)         | 0 to +50                                                   |

Warranty Years 3



Unit 7 Target Park, Shawbank Road,  
Lakeside, Redditch B98 8YN United Kingdom  
T: +44 (0)1527 515150 | F: +44 (0)1527 515143  
E: info@espuk.com | W: espuk.com

CLICK OR SCAN



CLICK OR SCAN