

MAGFIRE

Technical Specification



Product Code: CSD2

Luckinslive 391457650

Description: Combined Optical Smoke and Fixed Heat Detector for MAG Fire Panels



General Information

Dimensions (mm)	ø102 x 48 (Including Base)
Test Facility	Simulated Smoke/ Heat
Class	A1R
Weight (Kg)	0.17 (Including Base)
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	9 - 30
Cable Size (mm²)	0.4 - 2.0 (Twin)
Alarm Current @ 24V (mA)	49
Standby Current @ 24v (µA)	<60
Wiring Type	4-Wire Conventional

Environment

Ingress Protection	IP30
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Accessories

ZRL2: LED Indicator Plate

Features

Compatible with MAG2, MAG2P, MAG4, MAG4P, MAG816, and MAGPRO-CZM

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuke.com | W: espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN