

Product Code: D2411WH

Description: 5W LED Emergency Downlight Corridor Lens



General Information

Dimensions (mm)	Ø55 x 31
Emergency Module Dimensions (mm)	180 x Ø32
Battery Dimensions (mm)	70 x Ø31
Emergency Module Cutout (mm)	Ø48
Colour	White
RAL	RAL 9003
Materials	Polycarbonate Lamp Head & Housing
Mounting	Recessed
Weight (Kg)	0.25
Warranty (Years)	5

Supply & Power

Supply Voltage (V AC)	220 - 240
Frequency (Hz)	50
Electrical Safety	Charge & Discharge Protection
Power Consumption (W)	4.3
Power Consumption (A)	0.036

Environment

Ingress Protection	IP20
--------------------	------

- Features**
- Non-maintained operation
 - High power 5W LED
 - Charge and discharge protection
 - Green LED charging indicator
 - Corridor lens
 - Supplied with white aluminium bezel
 - 3.2V 6000mAh LiFePO4 Battery
 - BS EN 60598-2-22 standards

Luminaire Output

Colour Temperature (K)	5500
Emergency Luminous Flux (Lm)	214
LED Lamp Type	High Power 5W LED
LED Life (Hours)	40000

Emergency Information

Emergency Operation	Non-Maintained
Status Indication	Green LED
Replacement Battery	D002E
Battery Specification	3.2V 6000mAh LiFePO4
Battery Duration (Hours)	3

