

Product Code: D5403WH

Luckinslive 437084770

Description: 3W LED Emergency Downlight with Open and Corridor Lens



General Information

Dimensions (mm)	169 x 169 x 50
Colour	White
Materials	Polycarbonate Housing
Mounting	Ceiling or Wall Mounted - flush kit available
Weight (Kg)	0.4
Warranty (Years)	5

Supply & Power

Supply Voltage (V AC)	220 - 240
Frequency (Hz)	50
Electrical Safety	Charge & Discharge Protection
Power Consumption (W)	3

Environment

Ingress Protection	IP44
--------------------	------

Accessories EMSTSDLFLUSH: Flushing Kit

- Features**
- Self test facility
 - Maintained & non-maintained operation
 - High power 3W LED
 - Charge and discharge protection
 - Green LED charging indicator
 - Supplied with open & corridor lens'
 - 3.2V 1500mAh LiFePO4 battery
 - BS EN 60598-2-22 standards

Luminaire Output

Colour Temperature (K)	5500
Mains Luminous Flux (Open Lens)(Lm)	147
Mains Luminous Flux (Corridor Lens)(Lm)	138
Emergency Luminous Flux (Opens Lens)(Lm)	118
Emergency Luminous Flux (Corridor Lens)(Lm)	110
LED Lamp Type	High Power 3W LED
LED Life (Hours)	40000

Emergency Information

Emergency Operation	Maintained or Non-Maintained
Status Indication	Green LED
Replacement Battery	D001
Battery Specification	3.2V 1500mAh LiFePO4
Battery Duration (Hours)	3

