



DEC0802

8MP DECODER, 2 OUT HDMI



4K HDMI decoder, 2 HDMI video outputs, device used to create video wall and picture-in-picture multiscreen displays. Integration with Comelit VMS.



DEC0802

8MP DECODER, 2 OUT HDMI

MAIN FEATURES

Video output	1 x HDMI (4K max), 1 x HDMI (FULL-HD max)
--------------	---

SOFTWARE/FIRMWARE SPECIFICATIONS

Video compression	H.264, H.265
Frame rate	25fps
Operating system	Linux embedded

HARDWARE SPECIFICATIONS

Audio Inputs/Outputs	1/1
Type of connections/ports	2xUSB 2.0, 1xUSB 3.0, 2xEthernet 10/100/1000 Mbit/s, RS485

GENERAL DATA

Supply voltage	12VDC
Depth (mm)	268
Product weight (g)	2000
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-20 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply

CONNECTIVITY

RJ45 ports (n°)	2
-----------------	---

GENERAL FEATURES

Type of power supply	External power supply
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)