

Product Code: E855

Luckinslive 1907649

Description: Digital 4 Pin Time Switch, 96 Operations



General Information

Dimensions (mm)	146.5 x 105.7 x 82
Display	LCD
Timing Accuracy	5 Minutes / Year
Mounting	Surface Mounting
Base Type	4 pin
Warranty (Years)	5

Programming

Programming Schedule	7 Day Program
Available Operations	96 ON/OFF Periods
Summer/Winter Time Change	Yes (Automatic)
Holiday Mode	Yes
Temporary Override Facility (Manual Button)	Boost On for 2 hours or Advance Off Till Next Operation

Supply & Power

Supply Voltage (V AC)	230
Cable Size (mm²)	0.5 - 6
Power Reserve	20 Days
IEC Protection Class	Class II (Functional and Supplementary Insulation)

Environment

Ingress Protection	IP20
Operating Temperature (°C)	0 to +50

Accessories

110469: FD930 Conduit Box Time Switch

Outputs

Number of Outputs	1
Relay/Contact Type	SPST
Relay Voltage - Maximum (AC)	230
Output Relay Resistive Load Rating (A)	20
Maximum LED Lamp Load Rating (W)	3600 @ 230V
Maximum Inductive Current Rating (A) (0.8pf)	20
Maximum Incandescent, Halogen Lamp Load Rating (W)	1000
Maximum Fluorescent Lamp Load Rating (W)	860
Maximum Discharge (Sodium, Mercury, Metal Halide) Lamp Load Rating (W)	1600
Maximum Fluorescent Lamp Load Rating (W)	860

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuke.com | W: espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN