

FORT

Technical Specification

ESP
ScolmoreGROUP

Product Code: ECSPK4

Luckinslive 433240495

Description: Smart Security Alarm Kit with Hub, 4x PIRs, 2x Door Contacts and 2x Remote Fobs



Supplied

Fort Hub
Fort PIR x 4
Fort Door/Window Contact x 2
Fort Remote Control x 2
AC Adapter
Product Batteries
Mounting Screws & Wall plugs
User Guides

Component 1

ECSPHB - Smart Alarm Hub with Battery Backup

Quantity

1

General Information

Dimensions (mm)	109.5 x 109.5 x 40
Colour	White
Materials	ABS
Mounting	Surface
Available Operations	Home/Arm/Disarm/SOS
Sounder Output (dB)	95
Maximum Devices	32
Weight (Kg)	0.25

Supply & Power

Operating Voltage (V DC)	12
Power Consumption (A)	1
Battery Specification	7.4V 600mAh Lithium Polymer
Power Reserve	8 Hours (Approx.)

Camera & Recording

--	--

Transmission

Router Transmission Frequency (GHz)	2.4 (IEEE 802.11 b/g/n)
Router Transmission Range (m)	150
Transmission Frequency (MHz)	433

Auxillary

GSM	Yes (Full-size SIM Card)
GSM Frequency (MHz)	850, 900, 1800 & 1900

Environment

Operating Temperature (°C)	-10 to 55
----------------------------	-----------

Component 2

ECSPPIR - Smart Security PIR

Quantity

4

General Information

Dimensions (mm)	107 x 53 x 32
Bracket Dimensions (mm)	52 x 30 x 26.5
Colour	White
Materials	ABS
Mounting	Surface
PIR Range (m)	8
Transmission frequency (MHz)	433
Operating Voltage (V DC)	3
Power Consumption (A)	0.0095
Battery Type	AA (LR06) x 3
Power Reserve	12 Months (Approx.)
Zone Types	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/Home delay mode
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.046

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN

Product Code: ECSPK4

Luckinslive 433240495

Description: Smart Security Alarm Kit with Hub, 4x PIRs, 2x Door Contacts and 2x Remote Fobs

Component 3		Quantity
ECSPCT - Smart Door / Window Contact Sensor		2
General Information		
Dimensions (mm)	55.7 x 30.3 x 16	
Colour	White	
Materials	ABS	
Mounting	Surface	
Magnet Dimensions (mm)	25 x 10 x 9	
Transmission Frequency (MHz)	433	
Operating Voltage (V DC)	3	
Power Consumption (A)	0.015	
Battery Type	CR2477	
Power Reserve	12 Months (Approx.)	
Zone Types	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/Home delay mode	
Operating Temperature (°C)	-10 to 55	
Relative Humidity Resistance (%)	<80 (non-condensing)	
Weight (Kg)	0.2	
Warranty Years		1

Component 4		Quantity
ECSPRC - Smart Alarm Remote Control		2
General Information		
Dimensions (mm)	57 x 31 x 11	
Colour	Black	
Materials	ABS	
Available Operations	Home/Arm/Disarm/SOS	
Transmission Frequency (MHz)	433	
Operating Voltage (V DC)	3	
Battery Type	CR 2025	
Power Consumption (mA)	<7	
Power Reserve	12 Months (Approx.)	
Operating Temperature (°C)	-10 to 55	
Relative Humidity Resistance (%)	<80 (non-condensing)	
Weight (Kg)	0.02	