

Exitguard

EX125i-T

The **Exitguard EX125i-T** is designed specifically for integration with Grade 2 EN50131 intruder alarm systems.

Selectable resistors (1k + 1k or 2k2 + 4k7) ensure compatibility with various intruder alarm panels such as Honeywell, Pyronix, Texecom and Castle. The unit communicates alarms and faults to the main system via a supervised loop with separate alarm output. It also features auto sounder reduction to minimise noise after a preset period, with the sounder only restarting if the door is reopened.

The **Bleep In Off (BIO)** function provides an audible and visual alert when the unit is turned off, reducing the chances of it being forgotten.

Specification	EX125i-T
Audible Alarm Indication	Yes
Selectable Tones	Yes
Visual Alarm Indication	Yes
Audible/Visual off Indication	Yes
Enclosure	ABS
Sounder Output @ 1m	108 dB
Supervised Loop On/Off monitor	Yes
Supervised Loop Alarm Output	Yes
Keyswitch Control	Yes
Unit Tamper	Yes
Compatibility	All key intruder panels
Dimensions	175 x 125 x 60 mm
Replacement Key Barrels	Yes
Country of Manufacture	United Kingdom
Approvals	UKCA and CE marked, ROHS compliant

Benefits and Features

- Designed for Grade 2 intruder systems
- High power piezo sounder 108dB @1m
- Selectable alarm tones
- Visual Alarm Indication
- Keyswitch control with random key numbers
- Audible / visual warning when turned off (BIO)
- Supervised loop for On/Off monitor & separate Alarm output
- Safe Set to minimises false alarms
- Tamper switch
- Selectable resistor values for outputs
- Simple function change by internal jumpers
- Compatible with key panel manufacturers

All Exitguards are supplied with fixings, door contact, 1 metre of cable and a door warning sign.



Dimensions (mm)

