



Component 1

EZTAG3 - Proximity & Keypad Door Entry

Quantity

1

General Information

Dimensions (mm)	150 x 44 x 24
Colour	Silver
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Distance (mm)	<50
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlit	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

Supply & Power

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

Programming

PIN Length	2 - 6 Digits
------------	--------------

Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	---

Environment

Ingress Protection	IP65
--------------------	------

Component 3

A1EXIT - Flush Push to Exit Release Button

Quantity

1

General Information

Dimensions (mm)	86 x 86 x 22
Finish	Brushed Steel
Materials	Stainless Steel
Mounting	Surface or Flush (Backbox not Included)
Relay Voltage	125-250V
Contact Type	2 x SPST (Normally Open & Normally Closed)
Output Relay Rating	3A @125-250V AC
Operating Temperature (°C)	-20 to +55

Component 2

EVBPSBB - Power Supply Unit with Battery Backup

Quantity

1

General Information

Dimensions (mm)	129 x 73 x 50
Materials	ABS
Mounting	Surface
Supply Voltage (V AC)	100 - 230
Output Type	Configurable Normally Open or Normally Closed
Number of Outputs	Configurable Normally Open or Normally Closed2 (1 xSwitched & 1 xConstant)
Lock output	12V DC @ 1.5A
Ingress Protection	IP20

Component 4

A1ECP - Green Internal Emergency Call Point

Quantity

1

General Information

Dimensions (mm)	87.5 x 87.5 x 32
Colour	Green
Materials	Fire Resistant ABS
Mounting	Surface or Flush (Backbox Included)
Contact Type	Double Pole Double Throw
Output Relay Rating	3A @125-250V AC
Operating Temperature (°C)	-20 to +55
Weight (Kg)	0.17



Product Code: EZT3K

Luckinslive 435729736

Description: Single Internal Door Proximity Keypad Kit c/w Flush Exit Button

Component 5	Quantity
A1ML250 - Internal 250kg Holding Force Magnetic Lock with Z and L Brackets	1

General Information	
Dimensions (mm)	48 x 250 x 27
Colour	Silver
Materials	Aluminium Alloy
Mounting	Surface Only
Maximum Holding Force (Kg)	250
Operating Voltage (V DC)	12 & 24
Operating Temperature (°C)	-20 to +50

Warranty Years	2
----------------	---

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue

DoC

Installation

Quick Start

CLICK OR SCAN