

Product Code: EZT3KXTB

Luckinslive 435370156

Description: Single External Door Proximity Keypad Kit c/w IP55 Mushroom Exit Button



Supplied

1 x EZTAG3B
1 x EVBPSBB
1 x EVEXITMIP55
1 x EVEBGEXT2
1 x A1ML300XT

Component 1

Quantity

EZTAGB - Proximity & Keypad Door Entry

1

General Information

Dimensions (mm)	150 x 44 x 24
Colour	Black
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Distance (mm)	<50
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlit	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

Supply & Power

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

Programming

PIN Length	2 - 6 Digits
------------	--------------

Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	---

Environment

Ingress Protection	IP65
--------------------	------

Component 2

Quantity

EVBPSBB - Power Supply Unit with Battery Backup

1

General Information

Dimensions (mm)	129 x 73 x 50
Materials	ABS
Mounting	Surface
Supply Voltage (V AC)	100 - 230
Output Type	Configurable Normally Open or Normally Closed
Number of Outputs	Configurable Normally Open or Normally Closed2 (1 xSwitched & 1 xConstant)
Lock output	12V DC @ 1.5A
Ingress Protection	IP20



Product Code: EZT3KXTB

Luckinslive 435370156

Description: Single External Door Proximity Keypad Kit c/w IP55 Mushroom Exit Button

Component 3

Quantity

EVEXITMIP55 - Push to Exit Mushroom Release Button IP55

1

General Information

Dimensions (mm)	85 x 80 x 85
Materials	ABS
Mounting	Surface Only
Maximum Cable Size (mm ²)	2.5
Relay Voltage	30V
Contact Type	Normally Open & Normally Closed
Output Type	Clean Contact
Ingress Protection	IP55
Operating Temperature (°C)	0 to +50
Weight (Kg)	0.2

Component 4

Quantity

EVEBGEXT2 - IP67 Surface Green Emergency Resettable Call Point

1

General Information

Dimensions (mm)	89 x 89 x 72
Colour	Green
Materials	Polycarbonate
Mounting	Surface Only
Maximum Cable Size (mm ²)	2.5
Contact Type	Double Pole Double Throw
Output Type	Clean Contact
Output Relay Rating	3A (12 to 24V DC & 125 to 250V AC)
Ingress Protection	IP67
Operating Temperature (°C)	-25 to +65
Weight (Kg)	0.282

Component 5

Quantity

A1ML300XT - External 300kg Holding Force Magnetic Lock with Z and L Brackets

1

General Information

Dimensions (mm)	47 x 220 x 28
Colour	Silver
Materials	Aluminium Alloy
Mounting	Surface Only
Maximum Holding Force (Kg)	300
Operating Voltage (V DC)	12 & 24
Ingress Protection	IP68
Operating Temperature (°C)	-20 to +50

Warranty Years 2

