



Supplied

Keypad and Mounting Bracket
Screws and Wall Plugs
Diode and Capacitor
User Manual
10 x fobs

Component 1

EZTAG3 - Proximity & Keypad Door Entry

Quantity

1

General Information

Dimensions (mm)	150 x 44 x 24
Colour	Silver
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Distance (mm)	<50
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlit	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

Supply & Power

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

Programming

PIN Length	2 - 6 Digits
------------	--------------

Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	---

Environment

Ingress Protection	IP65
--------------------	------

Component 2

EZT3ST10 - Proximity Fobs

Quantity

10

General Information

Colour	Blue
Fob Reader Operating Distance (mm)	<50

Warranty Years 2

Accessories

EVBPBB: 12V Lock power supply with battery backup
A1SL: Fail Secure Flush Strike Lock
A1SLS: Fail Secure Surface Strike Lock
EVEXITC: Contactless Exit button
EVEXITM: Push to Exit Mushroom Release Button
EXEVITMIP55: Push to Exit Mushroom Release Button IP55
EXEBGEXT2: External Emergency Break Glass
A1ECP: Internal Emergency Call Point
A1EXIT: Flush Push to Exit Release Button
A1ML250: Internal 250kg Holding Force Magnetic Lock with Z and L Brackets
A1ML300XT: External 300kg Holding Force Magnetic Lock with Z and L Brackets

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN