

HDVIEW IP

Technical Specification



Product Code: H512VDGA

Luckinslive 436191732

Description: HDview IP PoE Varifocal 2.8-12mm Motorised Lens Dome Camera Anti-Vandal Grey



General Information

Dimensions (mm)	128 x 100 x 128
Colour	Grey & Black
Materials	Metal & Polycarbonate
Mounting	Surface
Impact Rating (IK)	IK10
Weight (Kg)	0.66
Warranty (Years)	2

Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	8
Other Power Sources	PoE (IEEE802.3af)

Media Information

Effective Pixels	5MP (2880 x 1620)
Sensor Size (")	1/2.7" Progressive CMOS
Lens size (mm)	2.8-12
Lens Type	Varifocal (Motorised)
Viewing Angle (°)	96.4 - 32.7
Electronic Shutter Type	Auto / Manual
Speed (sec/°)	1 to 1/100000
Scanning System	Progressive Scan CMOS
Frames Per Second (FPS)	5MP (2880*1620), Max 25fps 4MP (2560*1440), Max 25fps 3MP (2304*1296), Max 30fps 1080P (1920*1080), Max 30fps
Maximum IR Distance (m)	40
IR Wavelength (nm)	850
Video Bit Rate	128 Kbps - 8 Mbps
Microphone Supported	Built-in
Day/Night	IR-Cut filter with Auto Switch (ICR)
Hardware Reset Button	Built-in
Basic Detection	Cross line, intrusion(based on human body detection), Motion Detection, Ultra Motion Detection, Tampering alarm, Audio Detection
Intelligent Detection	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP authentication

Network

Interface	1 RJ45; 10/100M Base-TX Ethernet
ONVIF Compliant	Yes; Profile S, Profile G, Profile T
Network Functions	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP, SSL/TLS

Supplied Quick Start Guide, Mounting Guide, Installation Screws and Rawlplugs and Pass Through Gland

Compatible Products The range of 24/7 Network Video Recorders 4, 8, 16, 32 and 64 Channels

Accessories

DBG4: HDview IP 5MP Dome Deep Base Grey

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Quick Start



CLICK OR SCAN