

HDVIEW IP

Technical Specification



Product Code: HC832R8TB

Luckinslive 434802256

Description: HDview IP 32 Channel 8MP 24/7 8TB Network Video Recorder (NVR)



General Information

Dimensions (mm)	362 x 400 x 74
Weight (Kg)	<5
Warranty (Years)	2

Supply & Power

Operating Voltage (V AC)	100 - 240
Power Consumption (W)	<15 (Without Hard Disk)

Inputs & Outputs

Serial Ports	1 x RS485
Alarm Inputs	16
Alarm Outputs	4
PoE Ports	16
Video Input Channels	32
Audio Output Channels (RCA)	1
PoE Standards	IEEE 802.3at & IEEE 802.3af
Max. PoE Consumption Available (W)	30 (Per Port), 150 (Total)

Media Information

Display Video Output	1 x HDMI, 1 x VGA
Display Split	1, 4, 6, 8, 9, 16, 25 & 36
Display Resolutions	HDMI: 4k (3840x2160(30Hz), 1920x1080(60Hz), 1920x1080(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz) VGA: 1920x1080(60Hz), 1920x1080(50Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz)
Sync Playback	32 Channel
Data	RS485

Network

Network Connection	1 RJ45 10M, 100M, 1000M self-adaptive Ethernet Interface
Network Functions	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP
USB Interface	1 x USB (2.0), 1 x USB (3.0)

Supplied USB Mouse, Quickstart Guide, C13 Mains Cable, Server Mounting Brackets & Screws x 2, Auxiliary Terminal Block x 4, Rubber Feet x 4

Compatible Products The range of 24/7 HDview 5MP and 8MP and Rekor IP 2MP Cameras

Accessories

IPIN1POE: 1 Channel POE Injector
IPSW4POE: 4 Channel POE Switch
IPSW8POE: 8 Channel POE Switch

Features

Corridor Mode Screen (3 & 4), FTP, Schedule, Event Screenshots, Supports ONVIF (Profile S, G, T) Cameras

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN