

HDVIEW IP

Technical Specification



Product Code: HC84R4TB

Luckinslive 434802120

Description: HDview IP 4 Channel 8MP 24/7 4TB Network Video Recorder (NVR)



General Information		Recording	
Dimensions (mm)	240 x 260 x 47	Maximum Capacity	8TB
Weight (Kg)	<1 (Without HDD)	Internal HDD	4TB (1 x SATA)
Warranty (Years)	2	Recording Resolution	4k, 5MP, 4MP, 3MP, 1080p, 960p, 720p, D1, 2CIF, CIF
Supply & Power		Environment	
Operating Voltage (V DC)	48	Operating Temperature (°C)	-10 to +55
Power Consumption (W)	<9 (Without Hard Disk)	Relative Humidity Resistance (%)	≤ 90% RH (non-condensing)
Inputs & Outputs			
PoE Ports	4		
Video Input Channels	4		
Audio Output Channels (RCA)	1		
PoE Standards	IEEE 802.3at & IEEE 802.3af		
Max. PoE Consumption Available (W)	30 (Per Port), 54 (Total)		
Media Information			
Display Video Output	1 x HDMI, 1 x VGA		
Display Split	1 & 4		
Display Resolutions	HDMI; 3840x2160(30Hz), 1920x1080p(60Hz), 1920x1080p(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz) VGA; 1920x1080p(60Hz), 1920x1080p(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz)		
Sync Playback	4 Channel		
Network			
Network Connection	1 RJ45 10M, 100M self-adaptive Ethernet Interface		
Network Functions	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP		
USB Interface	1 x USB (2.0), 1 x USB (3.0)		
Supplied			
USB Mouse, Quickstart Guide, AC Adapter			
Compatible Products			
The range of 24/7 HDview 5MP and 8MP and Rekor IP 2MP Cameras			
Accessories		Features	
IPIN1POE: 1 Channel POE Injector IPSW4POE: 4 Channel POE Switch IPSW8POE: 8 Channel POE Switch		Corridor Mode Screen (3 & 4), FTP, Schedule, Event Screenshots, Supports ONVIF (Profile S, G, T) Cameras	

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuke.com | W: espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN