

**IPNVR004A08PB****4CH NVR, 8MP, POE, AI, 1TB HDD**

Network video recorder (NVR) for 4 IP channels (4 PoE), max. resolution 8MP, video compression H.265 / H.264, dual streaming, bandwidth 40Mbps. Supports all DVA video analysis functions for the connected cameras. Number plate database. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. 48 V power supply unit included. This NVR connects to Comelit servers protected by AWS services.



IPNVR004A08PB

4CH NVR, 8MP, POE, AI, 1TB HDD

MAIN FEATURES

Video inputs	4 PoE (4K/5MP/4MP/3MP/2MP/HD)
Main video output	1 (VGA - 1920x1080@60Hz), 1 (HDMI - 4K@30Hz)
Audio Inputs/Outputs	1 (RCA) / 1 (RCA) (G.711u / G.711a)
Video compression	H.264, H.265
Playback / recording frame rate	30fps@8MP
HDD supplied size	1TB (8TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Operating system	Linux embedded
Recording methods	Automatic, manual, programmed, event
Recording type	Dual streaming
Maximum number of channels being played simultaneously	1@4K, 4@FULL-HD
Protocols supported	DDNS, Comelit DNS, DHCP, NTP, PPPoE, SMTP, TCP/IP, UPnP, ONVIF
IP assignment	Manual, DHCP
Encrypted transmission	HTTPS, SSL, RSA+AES
Max bandwidth (Mbps)	40
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	5
Main functions	Video analysis (only with dedicated cameras), Car park management function, Alarm system function

FUNCTIONS

Motion detection	396
Anti-tampering	Yes
Privacy zones (n°)	4



IPNVR004A08PB

4CH NVR, 8MP, POE, AI, 1TB HDD

FUNCTIONS

Loss of video signal	Yes
System log	Yes
E-mail notification	Yes
Pre-event recording	5 seconds

HARDWARE SPECIFICATIONS

Type of connections/ports	1 x Ethernet 10/100/1000 Mbit/s, 4xEthernet 10/100 Mbit/s PoE (IEEE 802.3af), 2xUSB 2.0, 1xRS485
Fanless	Yes

GENERAL DATA

Max absorption (W)	11
Maximum absorption per POE port (W)	13
POE total power (W)	40
Maximum distance in long range mode (CAT5e/CAT6) (m)	180
Supply voltage (VAC)	100÷240, 50÷60Hz
Height (mm)	52
Width (mm)	300
Depth (mm)	248
Product weight (g)	1300
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse
System backup	USB 2.0