

CCTV ACCESSORIES

Technical
Specification
PoE



Product Code: IPX100POE

Luckinslive 425257357

Description: Single Channel PoE Extender



General Information

Dimensions (mm)	83 x 51.5 x 24
Materials	Aluminium Alloy
Weight (Kg)	0.088
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	48 - 57
Input Type	PoE

Inputs & Outputs

PoE Output (W)	15.4
----------------	------

Network

Connections	RJ45 Input RJ45 Output
Working Status	PoE Indicator, Link/Act Indicator

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-10 to +55
Storage Temperature (°C)	-40 to +85

Accessories CABIP10: 10M Data Cable Pre-Terminated with RJ45
CABIP20: 20M Data Cable Pre-Terminated with RJ45
CABIP40: 40M Data Cable Pre-Terminated with RJ45
CABIP80: 80M Data Cable Pre-Terminated with RJ45

Features Supports IP POE cameras on long cable runs up to 300 metres
One extender is required every 100 metres to achieve the maximum distance with no local power supply required
Plug and play installation
One input and one output PoE
Bandwidth 10/100Mbps
Short circuit and overload protection
Requires PoE supply from NVR or network switch

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN