TITLE:
Cat5e 4pr UTP

CODE:
SFX/C5-UTP-LSZH-D-WHT-305

DESCRIPTION:
305m Category 5e, 4pr UTP White LSZH
HDBaseT Certified

SUPPLIED AS:
Reel of 305m

LSZH SHEATH

HDPE INSULATION

COPPER

NYLON RIP CORD

FLAME-FLEX Drum-Roll LUCKINS epim EDA ELECTRICAL DISTRIBUTORS' ASSOCIATION UKAS KNX MEMBER cai CPR Compliant UKCA

Product Specification

Cable Construction

CPR	Dca -s2 -a1 -d2
Conductor	Bare Copper
Conductor Diameter (mm)	0.47 ±0.01
Overall Diameter (mm)	4.80 ±0.03

Insulation

Insulation	HDPE
Insulation Colour	Blue/White/Blue;Orange/White/Orange;Green/White/Green;Brown/White/Brown
Insulation Thickness (mm)	0.18

Outer/Jacket Specification

Jacket	LSZH
Overall Colour	White
Overall Diameter (mm)	4.80 ±0.03
Jacket Colour	White RAL 9003
Jacket Thickness (mm)	0.49 ±0.03
Nylon Rip-Cord	White 210D

Electrical Characteristics

Max Conductor DC resistance @ 20°C	<115O/km
Rated Temperature (°C)	-40°C to 70°C

MORE INFORMATION:

Sorry, no more information is available for this product

FLAME-FLEX®   Drum-R))ll   LUCKINS™   epim   EDA ELECTRICAL DISTRIBUTORS' ASSOCIATION   KNX MEMBER   cai   CPR Compliant   UKCA