



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



The kit includes: two Mini series door-entry phones art. 2702W, one transformer art. 1200, one Extra series external unit with 2 call buttons art. ET5002. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the relevant accessories supplied with the kit.

AWARDS





KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

PRODUCTS IN THE KIT



ET5002 EXTRA 4+N. SERIES ENTRANCE PANEL KIT. 2 BUTTONS

Extra series external unit with 2 call buttons. Stainless steel cover and white nameplate backlighting. Complete with flush-mounted box and wall bracket. Dimensions 95 x 135 x 6.5 mm (flush) - 25 mm (surface). 5-Wire cabling.

GENERAL DATA

Width (mm)	95
Height (mm)	135
Depth (mm)	25
Flush-mounted	Yes
Wall-mounted	Yes

COMPATIBLE SYSTEMS

Traditional	Yes
-------------	-----

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Clamps	~* ~ 2 3 4 S1 S2

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK07
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



2701W 1-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Dimensions: 105x191x28 mm

GENERAL DATA	
Width (mm)	103
Height (mm)	190
Depth (mm)	30
Product weight (g)	260
Product color	White
Wall-mounted	Yes
Desk base-mounted	Yes
COMPATIBLE SYSTEMS	
Traditional system	Yes
AUDIO FEATURES	
Microphone	4mm (Ø), Omnidirectional
ELECTRICAL CHARACTERISTICS	
Supply voltage	15÷16VDC
HARDWARE FEATURES	
Clamps	S 2 3 4 P1
Total buttons (n°)	1
ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating	IP30
Operating temperature (°C)	-5 ÷ 40
GENERAL FEATURES	



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

Absorption during call (mA)	0.42
Absorption during communication (mA)	0.35
Key button function	Yes
Loudspeaker volume control	Yes
Microphone volume control	Yes
Ringtone volume control	Yes
Audio system	Yes
Electronic bell	Yes



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



1200 TRANSFORMER 10VA 0-230V/0-12V

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES	
Supply voltage	230 VAC
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9
GENERAL DATA	
Width (mm)	53
Height (mm)	95
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40
COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes
ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	15



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

ACCESSORIES



ET9150 FLUSH-MOUNTED BOX FOR EXTRA ENTRANCE PANEL KIT

Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm



ET9160 WALL BRACKET FOR EXTRA ENTRANCE PANEL KIT

Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm



1229 EXTENSION SOUNDER

Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfacemounted or on civil series 503 box. Dimensions: 110X75X29 mm.