



3 POSITION CALL POINTS KEY SWITCH - ORANGE

KEY SWITCHES

An expanded range of key switches that complement our market leading range of access control solutions.



KS-SV-3



KS-FVE-3

SPECIFICATION

KS-SV-3 / KS-FVE-3

- Latching 3 Position operation
- Key removal in all positions
- Keyed alike
- Supplied with 2 x keys (606)
- Voltage free contacts
- Contact Rating: 4A 125VAC & 2A 250VAC
- Contact Rating: 2A 12/24VDC
- Operating Temp: -20 to +55C
- Rated IP54 ingress protection
- Etched legend (0 - 1)
- Security screws

FEATURES

KS-SV-3 / KS-FVE-3

- Orange Plastic
- SV = SMOKE VENT
- FVE = FIRE VENT EXTINGUISHANT
- Easy to operate
- Use for secure override
- Easy clean surface
- Footprint for mounting onto flush back box

OTHER PRODUCTS

SMART-G3



B-MCP-2N



EXI-S4PP/EA



EDR-IL-TP



DIMENSIONS

KS-SV-3 / KS-FVE-3

- 90x90x55/45 (mm) (HxWxD)
- 260g (Boxed)
- 212g (Unboxed)

CONTENTS

KS-SV-3 / KS-FVE-3

- Key Switch
- Plastic Plate (2mm)
- 2 x Keys (A126)
- 2 Security Screws
- Allen Key
- Shrouded Surface Box



Manufactured by a BSIA Member