

MAGFIRE

Technical Specification



Product Code: MAG4

Luckinslive 389335030

Description: 4 Zone Metal Conventional Fire Panel



General Information

Dimensions (mm)	320 x 220 x 80
Maximum Detectors Per Zone	30
Thresholds for Zone Conditions (mA)	0 - 2 (Fault condition) 2 - 6 (Normal condition) 6 - 110 (Fire condition)
Call Points Per Zone	Unlimited
Weight (Kg)	3.5Kg (Without Battery)
Warranty (Years)	3

Supply & Power

Supply Voltage (V AC)	230
Power Availability (A)	0.7
Mains Fail Consumption (mA)	50
Standby Supply	Up to 12V 7Ah (Battery Calculation Required)

Inputs & Outputs

Detection Zone End Of Line	Custom EoL; MAG-EOL
Fault/Fire Relay	Volt free 500mA @ 24V (max load)
Auxiliary Output	24V DC (300mA fused)
Sounder 1 Output	24V DC (max 300mA fused) Monitored
Sounder 2 Output	24V DC (max 300mA fused) Monitored

Environment

Operating Temperature (°C)	-5 to +40
Storage Temperature (°C)	-20 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Compatible Products 4-Wire Conventional MAGFIRE Devices

Additional Information Integral sound alarm button
Enable/disable security key
One man walk test facility
Individual sounder circuit fault ID
Individual zone/sounder isolate
Class change facility

Accessories

BAT7: 12V 7Ah SLA Battery
MAGBAR2/4: Key & Barrel set

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuks.com | **W:** espuks.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN