

Product Code: MAGDUO2KIT

Luckinslive 406864248

Description: 2 Zone Two Wire Conventional Fire Alarm Kit



Component 1

Quantity

MAGDUO2 - 2 Zone 2-Wire Fire Alarm Panel

1

General Information

Dimensions (mm)	331 x 331 x 99
Materials	V0 rated ABS
Maximum Detectors Per Zone	Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone)
Sounders and Detectors Mixed on Zones	Yes
Auxiliary Output	24V DC @ 250mA
Maximum Cable Length Per Zone (m)	500
Weight (Kg)	2.25

Supply & Power

Supply Voltage (Va)	
Operating Voltage (V DC)	21 -31
Nominal Operating Voltage (V DC)	24
Nominal Operating Current (mA)	700
Standby Supply	2 x 12V 3.2 Ah SLA Battery (Sold Seperately)

Inputs & Outputs

Programmable Inputs	2; 3.3 Volts @ 10mA (Un-Monitored)
Zones	2; Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone)
Output Zones	2 (Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone))
Monitored Outputs	2
Monitored Output Ratings	Rated at 28V DC @ 250mA each
Unmonitored Outputs	2
Unmonitored Output Ratings	Fire & fault; 30V DC @ 1A each
2 Monitored Outputs	Rated at 28VDC @ 250mA each
2 UnMonitored Outputs	Fire & fault; 30VDC @ 1A each

Environment

Ingress Protection	IP30
Operating Temperature (°C)	+5 to +40
Storage Temperature (°C)	

Component 2

Quantity

MAGDUOSHDS - FlexiPoint Combined Smoke & Heat Detector with Sounder

6

General Information

Dimensions (mm)	ø107 x 75
Sound Output @ 1m (Low) (db)	70+
Sound Output @ 1m (High) (db)	90+
Operating Voltage (V DC)	18 - 32
Maximum Cable Size (mm²)	1.5
Wiring Type	2-Wire Conventional
Maximum Current Consumption	23.8mA
Ingress Protection	IP21C
Operating Temperature (°C)	-10 to +50



MAGDUO

Technical Specification



Product Code: MAGDUO2KIT

Luckinslive 406864248

Description: 2 Zone Two Wire Conventional Fire Alarm Kit

Component 3

MAGDUOSHDSS - FlexiPoint Combined Smoke & Heat Detector with Sounder & Strobe

Quantity

1

General Information

Dimensions (mm)	ø107 x 75
Sound Output @ 1m (Low) (db)	70+
Sound Output @ 1m (High) (db)	90+
Device Loading Units (DLU's) - High	16
Maximum Device Loading Units (DLU's)	8
Operating Voltage (V DC)	18 - 32
Maximum Cable Size (mm ²)	1.5
Wiring Type	2-Wire Conventional
Maximum Current Consumption	28.5mA
Operating Temperature (°C)	-10 to +50

Component 4

MAGDUOCP - Call Point

Quantity

2

General Information

Dimensions (mm)	87 x 87 x 53 (Surface) 87 x 87 x 25 (Flush)
Device Loading Units (DLU's)	16
Type of the frangible element	A
Operating Voltage (Battery Powered Panel)(V DC)	28 - 26
Maximum Cable Size (mm ²)	1.5
LED Operation Colour	Red
Wiring Type	2-Wire Conventional
Maximum Current Consumption	16.5mA
Operating Temperature (°C)	-10 to +50

Component 5

MAGDUOSHDRT - Head Removal Tool

Quantity

1

General Information

Colour	Black
Materials	ABS

Warranty Years 3

Supplied 2 x Battery leads (1 x Red, 1 x Black)
1 x Battery connecting Lead
1 x 315mA quickblow fuse
2 x panel keys
2 x 680 Ohm resistor
2 x 10K ohm Resistor
2 x 3.275K Ohm Resistors

Accessories

BAT32: 12V 3.2Ah SLA Battery
MAGDUOPK: 2 MAGDUO Panel Keys
MAGDUOPCPS: MAGDUO Software
MAGDUOBBB: Battery Expansion Box for MAGDUO

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



CLICK OR SCAN