

MAGDUO

Technical Specification



Product Code: MAGDUOIOR

Luckinslive 406864044

Description: Input / Output Module



General Information

Dimensions (mm)	146 x 87 x 41
Mount box Dimensions (mm)	146 x 87 x 32
Materials	Housing: UL94-V2
Device Loading Units (DLU's)	23
Maximum Device Loading Units (DLU's)	160
System Status Indication	Output Active LED (Red): On continuously when output active Status - End of Line/Input Active LED (Red): On continuously when input active, Flash once every 20 seconds for normal operation, Flash once every 5 seconds for End of Line.
Warranty (Years)	3

Supply & Power

Frequency (Hz)	50/60
Fuses	3.15A Antisurge 20mm Ceramic
Operating Voltage (Mains Powered Panel)(V DC)	25.5 - 35
Operating Voltage (Battery Powered Panel)(V DC)	30 - 26
Maximum Cable Size (mm ²)	1.5
Current Consumption (Quiescent)(mA)	0.207
Wiring Type	2-Wire Conventional

Inputs & Outputs

Output Relay Rating	30V DC @ 2A 250V AC @ 3A Max 3A Surge
---------------------	---

Environment

Ingress Protection	IP30
Operating Temperature (°C)	-10 to +45

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuke.com | **W:** espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN