

MAGDUO

Technical Specification



Product Code: MAGDUOSHDSS

Luckinslive 406864138

Description: FlexiPoint Smoke and Heat Detector with Sounder and Strobe



General Information

Dimensions (mm)	ø107 x 75
Device Loading Units (DLU's) - High	16
Maximum Device Loading Units (DLU's)	8
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	18 - 32
Maximum Cable Size (mm ²)	1.5
Current Consumption (Quiescent)(mA)	0.1
Current Consumption in alarm state (mA)	High 10.5, Low 4.9, Off 2.6
Maximum Current Consumption	28.5mA
Alarm Current @ 24V (mA)	15.5
Wiring Type	2-Wire Conventional

Inputs & Outputs

Sound Output @ 1m (Low) (db)	70+
Sound Output @ 1m (High) (db)	90+

Environment

Ingress Protection	IP21C
Operating Temperature (°C)	-10 to +50

Compatible Products Compatible with MAGDUO2, MAGDUO4 and MAGDUO8

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN