

MAGFIRE

Technical Specification



Product Code: MAGPRO-0i40

Luckinslive 399178999

Description: 4 Output Module With Isolator



General Information

Dimensions (mm)	126 x 176 x 57
Weight (Kg)	0.23
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	15 - 32
Cable Size (mm ²)	0.4 - 2.0
Current consumption in STAND-BY mode (µA)	175 (@27V DC)
Nominal Current Consumption (µA)	200 (@27V DC)
Current consumption with 1 LED ON (mA)	4

Inputs & Outputs

Number of Outputs	4
-------------------	---

Communication

Protocol Type	Custom (Closed)
---------------	-----------------

Environment

Ingress Protection	IP40
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Compatible Products Compatible with MAGPRO16, MAGPRO16G, MAGPRO96 and MAGPRO96G

Additional Information Used to switch equipment in conditions such as 'Common Fire'

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuke.com | **W:** espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN