

MAGFIRE

Technical Specification



Product Code: MAGPRO-10Si

Luckinslive 399179024

Description: Conventional Sounder Module with Isolator



General Information

Dimensions (mm)	126 x 176 x 57
Weight (Kg)	0.23
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	15 - 32
Cable Size (mm ²)	0.4 - 2.0
Current consumption in STAND-BY mode (µA)	270 (@27V DC)
Current consumption with 1 LED ON (mA)	3.6
Permissible Voltage Ripple (pp)	3.0V (@27V DC)

Inputs & Outputs

Zones	16
Type of Output	Monitored Conventional Sounder Circuit
Output Type	Monitored Conventional Sounder Circuit
Number of Outputs	1
Maximum Output Electrical Characteristics (DC)	28V (@0.75A)

Communication

Protocol Type	Custom (Closed)
---------------	-----------------

Environment

Ingress Protection	IP40
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Additional Information Requires 24V DC Supply, Not-Loop Powered

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN