

MAGFIRE

Technical Specification



Product Code: MAGPRO-4i00

Luckinslive 399179011

Description: 4 Input Module With Isolator



General Information

Dimensions (mm)	126 x 176 x 57
Weight (Kg)	0.23
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	15 - 32
Cable Size (mm ²)	0.4 - 2.0
Current consumption in STAND-BY mode (µA)	300 (@27V DC)
Nominal Current Consumption (µA)	330 (@27V DC)
Current consumption with 1 LED ON (mA)	4
Current consumption with 2 LED ON (mA)	7

Inputs & Outputs

Number of Inputs	4
Type of Inputs	Monitored
Zones	16

Communication

Protocol Type	Custom (Closed)
---------------	-----------------

Environment

Ingress Protection	IP40
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Supplied 8 x 56k Ohm Resistors

Additional Information Can be used to interface 4 x 3rd party devices to create conditions such as Class Change
Supplied with 56k End of Line Resistors

Features

Loop Powered

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuke.com | **W:** espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN