

MAGFIRE

Technical Specification



Product Code: MAGPRO-DB23W

Luckinslive 437271923

Description: MAGPRO Addressable Fire EN54-23 VAD Base White LEDs



General Information

Dimensions (mm)	ø114 x 27
Colour	White RAL 9016
Materials	Housing: ABS
Mounting	Ceiling
LED colour	White
Flash Rate	0.5Hz
Coverage Volume	C - 3-6
Weight (Kg)	0.08
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	20 - 32
Nominal Operating Voltage (V DC)	27
Cable Size (mm ²)	0.4 - 1.5
Maximum Consumption at Communication (µA)	650 (@27V DC)
Maximum Current Consumption	<19mA
Wiring Type	Analogue Addressable (MAGPRO)

Communication

Protocol Type	Custom (Closed)
---------------	-----------------

Environment

Ingress Protection	IP21C (with mounted MAGPRO-DBS1)
Operating Temperature (°C)	-10 to +50
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Compatible Products MAGPRO series of CIEs

Additional Information Requires MAGPRO-DBS1 to operate
Requires CIE firmware version of; MAGPRO16/G V6.6.2, MAGPRO96/G V4.5.2 & MAGPRO9601 1.1.3

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN